



13000 Temple Ave. City of Industry, CA 91746

Tech line (626) 968-5147 Main line (800) 237-7560
www.dcsports.com

CAI5516
COLD AIR INTAKE INSTALLATION INSTRUCTIONS
1992-1995 HONDA CIVIC DX, LX, EX, SI 1.6L

**!!! READ ALL INSTRUCTION THOROUGHLY BEFORE BEGINNING
INSTALLATION. FAILURE TO DO SO MAY RESULT IN COSTLY ENGINE
AND/OR SYSTEM DAMAGE!!!**

*****IF UNSURE ABOUT INTAKE SYSTEM INSTALLATION PLEASE HAVE A
REPUTABLE PERFORMANCE SHOP OR A LICENCED MECHANIC
INSTALL THIS SYSTEM*****

*****FOR YOUR SAFETY, ALLOW ENGINE TO COOL FOR AT LEAST AN
HOUR BEFORE BEGINNING INSTALLATION*****

*****PLEASE CHECK AND MAKE SURE ALL HARDWARE IS PRESENT
BEFORE INSTALLATION. PARTS LIST ON LAST PAGE*****

A.R.B INFORMATION

*****THIS DC SPORTS INTAKE ARE CARB EXEMPT
PER EO#D-370-13 FOR 1992-1995 HONDA CIVIC ONLY*****

TOOLS REQUIRERD

**Ratchet 10mm, and 11mm deep socket
Flat Screwdriver
Phillips Screwdriver
6" Extension
Pliers**

REMOVAL OF STOCK INTAKE AND INSTALLATION OF INTAKE SYSTEM

1. Loosen clamp on the throttle body securing the factory intake tube.
2. Unclip the wire harness and hoses clipped on the factory intake tube.
3. Remove the crankcase breather hose from the factory intake tube by pulling upwards.
4. Remove the air chamber in front of the OEM air box by pulling upwards.
5. Locate and remove three 10mm bolts securing the OEM air box to the chassis.
6. Remove factory intake tube and air box from vehicle.
7. Remove front bumper by removal of five screws on top of the bumper two screws on the side and two 10mm bolts underneath.
8. Remove the plastic splash shield covering the resonator box by locating two plastic 10mm bolts and one 10mm bolt and pull slash shield down.
9. Remove the resonator box by locating and removal of three 10 bolt securing the resonator box to the chassis.
10. Remove resonator box from vehicle.
11. **WARNING MAKE SURE ENGINE IS COOL BEFORE THESE NEXT STEPS.**
12. Remove the factory crankcase and coolant plumbing from vehicle.

13. With provided 8mm heater hose replace coolant hose that was just removed.
14. Install provided 2.50" coupler and two clamps onto the throttle body but only tighten the clamp towards the throttle body at this time.
15. Loosely install the DC Sports intake tube into the throttle body.
16. Notice the welded bracket on the intake tube. Install provided vibration mount between the bracket and the chassis.
17. Align the bracket on top of the vibration mount and use provided washer and nut to secure the intake tube.
18. Tighten remaining clamp on the throttle body and make sure the pipe is free from any obstructions.
19. Install the DC Sports air filter onto the intake tube.
20. Install provided 10mm vacuum hose onto the crankcase breather vent and onto the intake tube nipple.
21. Reinstall the bumper in reverse step of removal.
22. Installation is now complete check all work performed.

*****LIMITED 10 YEAR WARRANTY*****

DC Sports only warranty's intake systems due to poor workmanship. We do not cover normal wear and tear damages due to misuse or abuse. We do not warranty the finish of intake tubes.

Warranty covers the original owner of intake system by having proof of purchase. We have the right to void all warranty if you cannot provide the information needed by DC Sports.

*****CAUTION*****

DC Sports does not assume any liability for damage caused by rain or floods causing the intake system for taking on water. We recommend that you remove the cold air intake system due to wet conditions.

*****WARRANTY CLAIMS*****

All warranty claims must be shipped prepaid by the customer to DC Sports. Warranty claims must have an RMA (Return Merchandise Authorization) number on the box or package will be refused and sent back to the shipper.

PARTS LIST

Quantity	Part Number	Part Description
1	DCCAP5516	CAI5516 INTAKE TUBE
1	DCCP250	2.50" STRAIGHT COUPLER
18"	DCHH8MM	8MM HEATER HOSE
9"	DCVH10MM	10MM VACUUM HOSE
2	DCCL250	2.50" CLAMP
1	DCVM6MM	M6 M/M VIBRA MOUNT
1	DCF275	2.75" DC SPORTS FILTER PACK
2	DCDECAL	DC SPORTS DECAL

THANK YOU FOR CHOOSING DC SPORTS