



13000 Temple Ave. City of Industry, CA 91746

Tech line (626) 968-5147 Main line (800) 237-7560  
www.dcsports.com

## **CSB1004 Strut Tower Bar Installation Instructions**

### **1995-99 Mitsubishi Eclipse 2.0L Turbo Model ONLY**

**READ ALL INSTRUCTIONS THROUGH COMPLETELY BEFORE BEGINNING  
INSTALLATION.**

**IF YOU ARE NOT COMFORTABLE AND/OR FAMILIAR WITH THESE INSTRUCTIONS, PLEASE  
REFER THIS INSTALLATION TO A QUALIFIED PROFESSIONAL.**

1. With the car set on the ground, remove two (2) 10mm nuts on the left side shock tower and two (2) 10mm nuts on the right side shock tower (Remove the two (2) 10mm nuts from each side closest to the front side fenders). Set these four (4) 10mm nuts aside as they will be re-used.
2. Install the DC Sports Carbon Steel Strut Tower Bar over the shock tower studs on each side.
3. Re-install two (2) original 10mm nuts on the left side shock tower (Do not tighten) and two (2) original 10mm nuts on the right side shock tower (Do not tighten).
4. Tighten all four (4) 10mm nuts (Torque: 4.4 kg-m, 32 lb-ft).
5. Ensure that the DC Sports Carbon Steel Strut Tower Bar does not interfere with any parts of the vehicle.
6. **RECHECK ALL YOUR WORK.**

### **PARTS LIST**

<b>Quantity</b>	<b>Part Number</b>	<b>Part Description</b>
1	CSB1004	Carbon steel strut bar
2	DCS1008	DC Sports decals

**THANK YOU FOR CHOOSING DC SPORTS**