



13000 Temple Ave. City of Industry, CA 91746

Tech line (626) 968-5147 Main line (800) 237-7560
www.dcsports.com

CSB1205 Front Strut Tower Bar Installation Instructions

1989-1994 Nissan 240SX (S13)
w/ KA24E, KA24DE, SR20DET

**READ INSTRUCTIONS THROUGH COMPLETELY BEFORE BEGINNING
INSTALLATION.**

**IF YOU ARE NOT COMFORTABLE AND/OR FAMILIAR WITH THESE INSTRUCTIONS, PLEASE
REFER THIS INSTALLATION TO A QUALIFIED PROFESSIONAL.**

1. With the car set on the ground, remove three (3) 10mm nuts from the left side shock tower studs and three (3) 10mm nuts from the right side shock tower studs. Set these nuts aside as they will be re-used.
2. Install the DC Sports Front Strut Tower Bar by sliding the strut bar pads over the shock tower studs.
3. Re-install the three (3) original 10mm nuts to the left side shock tower studs and three (3) original 10mm nuts to the right side shock tower studs and tighten (Torque: 6.0 kg-m, 43 lb-ft).
4. **RECHECK ALL YOUR WORK.**

PARTS LIST

Quantity	Part Number	Part Description
1	CSB1205	Carbon steel strut bar
2	DCS1008	DC Sports decals

THANK YOU FOR CHOOSING DC SPORTS