

# Aden

The key design element of our LED cylinder is the removable lens. This feature allows for three distinctive styles during installation.



**ADA**  
COMPLIANT



**JA8**  
CERTIFIED



Model	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
<b>LEDWALL-A</b>	29 W	2100 lm	2260 lm	90	3000 K	120 V - 277 V

**Specifications**

Cylindrical housing made of extruded aluminum

Fixture canopy made of die-cast aluminum

LED module mounted on an aluminum heat sink to maximize heat dissipation and extend product life

Cylinder comes with 3 optical options:

- Bright aluminum reflector that provides a 45° beam spread
- Frosted glass lens to allow a wider beam spread
- Die-cast aluminum cap to allow a down light only version

Compatible with TRIAC, ELV and 0-10 V dimmers

The LED board is sealed with a clear tempered glass lens to ensure weatherproof operation

Baked powder paint coat for a highly durable finish

JA8 certified

ENERGY STAR certified

ADA compliant

Suitable for wet locations

Refer to website for dimmer compatibility

Ideal operating temperature:  
-20° to 40° C

5-year warranty

**Finish**

- **BK** Black
- **SG** Silver grey
- **WH** White

**Order example**

**LEDWALL-A-BK**

LEDWALL-A LED cylinder in a black finish

**Note**

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALs representative for more information.



**LEDWALL-A**

