

Excel smart

Our smart LED panel light will be a great addition to any project. The sleek and minimal construction allows for the easiest of installations with the added bonus of a wide range of colors and settings made possible by the DALI Connect App™.



DRY



CHANGE COLORS



Intertek



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
SM-PNL4WH	4"	10 W	600 lm	80+	RGB + 2700 K - 6500 K	120 V
SM-PNL6WH	6"	15 W	1000 lm	80+	RGB + 2700 K - 6500 K	120 V

Specifications

Includes a junction box with integrated driver
 Over 50,000 hours of service life
 Full color spectrum
 2700K - 6500K in pure whites
 Dimmable through the Dals Connect app only
 Minimal heat emission
 Aluminum construction
 Suitable for dry locations
 IC certification (suitable for direct contact with insulation)
 5-year warranty

Finish

○ WH White

Accessories

- REC-PT4-BB (SM-PNL4WH)**
4" recessed panel trim in brushed brass
- REC-PT4-BK (SM-PNL4WH)**
4" recessed panel trim in black
- REC-PT4-SN (SM-PNL4WH)**
4" recessed panel trim in satin nickel
- REC-SMPT6-BK (SM-PNL6WH)**
6" recessed panel trim in black
- SM-PNLEXT108**
108" extension for smart recessed panel lights

Order example

SM-PNL4


4" RGB+CCT smart fixture with embedded Wi-Fi-enabled controller which you can control with your smartphone



Download the Dals Connect app

Wi-Fi - no hub needed
 Create groups
 Set schedules
 Remote access
 Compatible with Google Assistant and Amazon Alexa



SM-PNL4

Ø4 1/4" 



SM-PNL6

Ø6 1/4" 