



# Bathroom Fan Heater



## Features

### Color

- Standard: white.

### Finish

- Standard: epoxy/polyester powder paint.

### Voltage

- 240/208V, 1-phase.

### Construction

- 20-gauge steel cabinet and front cover.
- High-limit temperature control with manual reset.

### Fan

- Quiet fan operating.
- Two-stage centrifugal blower delivering between 40 to 55 cfm.
- Motor totally isolated from the heating chamber.

### Heating element

- Stainless steel tubular heating element with aluminum fins, powder coated for better corrosion resistance in wet environments such as bathrooms.

### Control

- Built-in thermostat.
- Mechanical timer, 0-60 minutes.

### Installation

- Wall installation only.
- 4.5 in. (114 mm) minimum clearance to the floor but 12 in. (305 mm) is recommended for longer and cleaner performance.
- Wall mounting can with 7 knock-outs and 22 cubic in. wiring compartment.
- May be recessed in 2 in. x 3 in. stud partitions using the recess trim kit C1TKW.
- May be surface mounted using the surface mounting box C4TKW.

### Warranty

- 3-year warranty against defects.





### Application

- Bathroom.

## Model

Product #	Volts	Watts <sup>1</sup>	Weight	
			lb	kg
CBC132TW	240/ 208	500/800/1300 375/600/975	8.0	3.6

<sup>1</sup> Multi-watt heater. Must be configured for the desired wattage before installation. Standard color is white.



ROUGH-IN: 8" W (203 mm) X 10-1/8" H (257 mm) X 4" D (102 mm)

## Options

Product # Kit	Description
C4TKW	4" surface mounting box
C1TKW	1" recess trim kit for installation in 2 in. x 3 in. stud partitions