



# Residential Fan Heater



## Features

### Color

- Standard: white.

### Finish

- Standard: epoxy/polyester powder paint.

### Voltage

- 120V, 240/208V, 1-phase.

### Construction

- 20-gauge steel cabinet and front cover.
- High-limit temperature control with manual reset.
- One-time over temperature thermal back-up fuse in case of fan motor failure.

### Fan

- Quiet fan operating.
- Two-stage centrifugal blower delivering between 40 to 55 cfm.
- Motor totally isolated from the heating chamber.

### Heating element

- Nickel-chromium alloy stitched wire protected by mica insulators.
- Heating element provides instant heat.

### Control

- Built-in thermostat available with a control knob.
- If an electronic thermostat is used, it must be compatible with forced-air heaters.

### Installation

- Wall installation for all models.
- Ceiling installation on models 1500W or less.

For a ceiling mount installation Global Commander highly recommends the use of a wall thermostat for superior temperature control.

Note: If an electronic thermostat is used, it must be compatible with forced-air heaters.





- 4.5 in. (114 mm) minimum clearance to the floor but 12 in. (305 mm) is recommended for longer and cleaner performance.
- Wall mounting can with 6 knock-outs and 34 cubic in. wiring compartment.
- May be recessed in 2 in. x 3 in. stud partitions using the recess trim kit C1TKW.
- May be surface mounted using the surface mounting box C4TKW.

### Warranty

- 2-year warranty against defects.

### Application

- Entrance way, kitchen, bathroom, family room, basement.



ROUGH-IN: 8" W (203 mm) X 10-1/8" H (257 mm) X 4" D (102 mm)

## Models

Product #		Volts	Watts	Weight	
Without Built-in Thermostat	With Built-in Thermostat <sup>1</sup>			lb	kg
CSC101W	CSC101TW	120	1000	7.0	3.2
CSC151W	CSC151TW	120	1500	7.0	3.2
CSC072W	-	240/208	750/563	7.0	3.2
CSC102W	CSC102TW	240/208	1000/750	7.0	3.2
CSC152W	CSC152TW	240/208	1500/1125	7.0	3.2
CSC202W	CSC202TW	240/208	2000/1500	7.0	3.2

## Options

Product # Kit	Description
C4TKW	4" surface mounting box
C1TKW	1" recess trim kit for installation in 2 in. x 3 in. stud partitions
CTT1W	Single-pole bi-metal thermostat, 5 °C (40 °F) to 30 °C (85 °F)
CTT2W	Double-pole bi-metal thermostat, 5 °C (40 °F) to 30 °C (85 °F)

<sup>1</sup> Single pole bi-metal thermostat, 5 °C (40 °F) to 30 °C (85 °F), factory installed.  
Standard color is white.