

$SLIMLED^{\text{m}}$ original



BACK TO THE BASICS

SlimLED Original, an entry-level fixture designed to meet both plenum and budget constraints. Small but mighty, the SlimLED original fixture boasts reliable spring loaded clips, a color selectable switch, wet location rating, and energy star. This ultra-thin fixture is packed with prime features making it optimal for hallways, closets, basements and more.



















FEATURES

- A slender, low-profile downlight
- Color temperature selectable switch on the driver (27 K, 30 K, 35 K, 40 K, and 50 K)
- 110° beam spread
- LED driver with 100-135V AC input
- "Quick connect" push-in terminals for fast and easy wiring
- Suitable for wet locations

SlimLED Original



DELIVERED

3": Up to 505 lm (7W)

4": Up to 680 lm (9W)

4" High Output: Up to 940 Im (12W)

5": Up to 1115 lm (15W)

6": Up to 1255 lm (16W)

TRIM FINISH











TRIM

3"



COLOR TEMPERATURE



Selectable 27, 30, 35, 40, 50 K

Accessories



SLM4-XLRING-BK(BK/WH)1

EXTRA LARGE TRIM RING FOR SLM4-CCT, METAL.



P-NCMK-1

HANGER BAR KIT. INCLUDES HANGER BARS, BRACKETS AND SCREWS.



VAPOUR BARRIER EXTENDER. FOR USE IN NEW CONSTRUCTION APPLICATIONS.



SLM4P-XLRING-BK(BK/WH)1

EXTRA LARGE TRIM RING FOR SLM4H-CCT, METAL.



VAPOUR BARRIER EXTENDER. FOR USE IN NEW CONSTRUCTION APPLICATIONS.





LC-CRTL-3WAY-1

ONCLOUD SMART Wi-Fi 3-WAY SWITCH. SUITABLE FOR 3-WAY OR 4-WAY SWITCH APPLICATIONS



P-3020 / P-4020 / P-5020 / P-6020

3-6" ROUND PRE-MOUNTING PLATE WITH DRIVER ATTACHMENT CLIP, FOR SLIMLED FIXTURES.



VBE-2*

VAPOUR BARRIER EXTENDER. FOR USE IN REMODEL APPLICATIONS.





LC-CRTL-DIM-1

ONCLOUD SMART Wi-Fi DIMMER. FEATURES AN ON/OFF PRESS AND A 7 LEVEL TOUCH SLIDER.



P-4024 / P-60241

41/4" AND 61/4" ROUND PRE-MOUNTING PLATE WITH DRIVER ATTACHMENT CLIP FOR 4" AND 6" SLIMLED FIXTURES.



VAPOUR BARRIER EXTENDER. FOR USE IN REMODEL APPLICATIONS.

*Available for SlimLED Original 3", High Output, and 4" only.

M-SLMORIGINAL-SS-E

