

MIR | MIRAGE™

CONVECTOR



MIRAGE™

THE MOST DISCREET ON THE MARKET!

The Mirage convector has a unique, modern and discreet look and offers unquestionable efficiency. Available with or without an ultra-precise integrated electronic thermostat and in several voltages, the Mirage is suitable for rooms in homes or businesses. With its simple facade and elegant design, the Mirage blends in with any decor.

BLENDS IN WITH ANY DECOR

STURDY ONE-PIECE FRONT PANEL

TOTALLY QUIET

BUILT-IN ELECTRONIC THERMOSTAT (OPTIONAL) WITH BACKLIT SCREEN

ADAPTS TO MULTIPLE MARKETS

AVAILABLE IN 120 V, 208 V, 240 V, 347 V AND 600 V

COLOURS

- **standard:** white, soft white
- **Orora (optional):** refer to www.stelpro.com/en-CA/Orora

FINISH

- epoxy-polyester powdercoat

MANUFACTURING

- 20-gauge steel cabinet and front
- the cabinet height improves the chimney effect
- bottom air intake and top air discharge
- 6 ft (2 m) 16 gage molded cable with 3-prong grounded, 120 V plug (MIR1501P model)

ELEMENTS

- two stainless steel tubular sheathed elements insulated with nylon sleeves reducing expansion and contraction noises

CONTROL

- electronic thermostat required: built-in electronic thermostat with LCD screen (optional) or electronic wall thermostat (not included)
- automatic temperature lowering at night (Automatic mode)
- maximum temperature setpoint lock option (Security mode)

INSTALLATION

- surface mounted only
- wall mounted at least 4 in. from the floor
- concealed mounting bracket (included)
- back entry plate with cable clamps (included)

WARRANTY

- five years, *three years on electronic components



ALSO AVAILABLE
EASY INSTALLATION WITH 120 V PLUG

IDEAL FOR:

kitchen, living room, bedroom, basement, commercial space, office

°STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at www.stelpro.com.



TECHNICAL SPECIFICATIONS

| BUILT-IN THERMOSTAT | | WITHOUT THERMOSTAT | | POWER | VOLTAGE | | HEIGHT | | LENGTH | | WEIGHT | |
|---|--|--------------------|-----|-----------|---------|-----|--------|-----|--------|-----|--------|--|
| CODE | | CODE | | WATTS | VOLTS | MM | IN. | MM | IN. | KG | LB | |
| MIR0501 | | MIR0501WC | | 500 | 120 | 457 | 18 | 444 | 17 1/2 | 5.3 | 11.75 | |
| MIR0508 | | MIR0508WC | | 500 | 208 | 457 | 18 | 444 | 17 1/2 | 5.3 | 11.75 | |
| MIR0502 | | MIR0502WC | | 500/375 | 240/208 | 457 | 18 | 444 | 17 1/2 | 5.3 | 11.75 | |
| --- | | MIR0503WC | | 500 | 347 | 457 | 18 | 444 | 17 1/2 | 5.3 | 11.75 | |
| MIR1001 | | MIR1001WC | | 1000 | 120 | 457 | 18 | 597 | 23 1/2 | 6.7 | 14.75 | |
| MIR1008 | | MIR1008WC | | 1000 | 208 | 457 | 18 | 597 | 23 1/2 | 6.7 | 14.75 | |
| MIR1002 | | MIR1002WC | | 1000/750 | 240/208 | 457 | 18 | 597 | 23 1/2 | 6.7 | 14.75 | |
| --- | | MIR1003WC | | 1000 | 347 | 457 | 18 | 597 | 23 1/2 | 6.7 | 14.75 | |
| --- | | MIR1006WC | | 1000 | 600 | 457 | 18 | 597 | 23 1/2 | 6.7 | 14.75 | |
| MIR1501 | | MIR1501WC | | 1500 | 120 | 457 | 18 | 749 | 29 1/2 | 8 | 17.75 | |
| MIR1508 | | MIR1508WC | | 1500 | 208 | 457 | 18 | 749 | 29 1/2 | 8 | 17.75 | |
| MIR1502 | | MIR1502WC | | 1500/1125 | 240/208 | 457 | 18 | 749 | 29 1/2 | 8 | 17.75 | |
| --- | | MIR1503WC | | 1500 | 347 | 457 | 18 | 749 | 29 1/2 | 8 | 17.75 | |
| --- | | MIR1506WC | | 1500 | 600 | 457 | 18 | 749 | 29 1/2 | 8 | 17.75 | |
| MIR2008 | | MIR2008WC | | 2000 | 208 | 457 | 18 | 902 | 35 1/2 | 9.4 | 20.75 | |
| MIR2002 | | MIR2002WC | | 2000/1500 | 240/208 | 457 | 18 | 902 | 35 1/2 | 9.4 | 20.75 | |
| --- | | MIR2003WC | | 2000 | 347 | 457 | 18 | 902 | 35 1/2 | 9.4 | 20.75 | |
| --- | | MIR2006WC | | 2000 | 600 | 457 | 18 | 902 | 35 1/2 | 9.4 | 20.75 | |
| MODEL WITH 120 V PLUG (RESIDENTIAL OUTLET) | | | | | | | | | | | | |
| MIR1501P* | | --- | --- | 1500 | 120 | 457 | 18 | 749 | 29 1/2 | 8 | 17.75 | |

Add W for white or SW for soft white (or consult the optional colour chart and contact your Stelpro representative for all other colours).
 Mechanical wall thermostats are not compatible with the without thermostat model (WC). An electronic thermostat is required. Models also available in 277 V and 480 V.
 * Available in white only
 --- not available

ACCESSORIES

| PRODUCT | DESCRIPTION |
|------------|--|
| MIRRE153* | built-in electronic low voltage relay [15 A @ 120 V-347 V] |
| MIRRE156* | built-in electronic low voltage relay [6 A @ 600 V] |
| MIRRE153T* | built-in electronic low voltage relay c/w transformer 24 V [15 A @ 208 V-347 V] |

Electronic relays can receive a PWM (pulsed width modulation) or digital (on/off) signal.
 * Factory installed



BUILT-IN ELECTRONIC THERMOSTAT AVAILABLE FOR THE 120 V TO 240 V MODELS

TECHNICAL DRAWINGS

