

# SK | AIR CURTAIN™

## CEILING FAN HEATER



**AIR  
CURTAIN™**



## HEAT FROM ABOVE

The Air curtain ceiling fan heater silently beams down heat from above. This unique model is ideal for rooms where wall space is limited. In bathrooms, the Air curtain can be installed just outside the shower or bathtub. With its ceiling-recessed casing, the Air curtain is an excellent way to provide discreet air circulation. The result: uniform heating and air movement, and reduction in mirror and window fog. By adding a wall timer, you can use it on demand.

### CEILING MOUNTED

IDEAL FOR ROOMS WITH LIMITED WALL SPACE

### HEATING ON DEMAND

OPTIONAL WALL TIMER

### COMPACT AND QUIET

### 347 V MODEL AVAILABLE

### COLOURS

- **standard:** white, soft white
- **Orora (optional):** refer to [www.stelpro.com/en-CA/Orora](http://www.stelpro.com/en-CA/Orora)

### FINISH

- epoxy-polyester powdercoat

### MANUFACTURING

- 22-gauge steel cabinet and 1/4 in. (6.4 mm) deep 20-gauge steel front grille
- easy access for maintenance (no screws)

### THERMAL PROTECTION

- thermal protection with automatic reset

### ELEMENT

- nichrome element produces instant heat

### CONTROL

- built-in thermostat (optional)
- wall thermostat (not included) – the use of an electronic thermostat is strongly recommended
- 60 minute timer (optional)

### INSTALLATION

- ceiling mounted (recommended height 8 ft., maximum 9 ft.)
- surface mounted with surface adapter (optional)
- recessed or surface mounted with adapter for suspended ceiling (optional)
- unit can be mounted parallel or perpendicular to ceiling beams
- approved to be recessed in mineral wool; for all other materials please check with insulating product manufacturer

### WARRANTY

- five years

### IDEAL FOR:

bathroom, entryway, daycare centre, room with limited wall space

°**STELPRO**

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at [www.stelpro.com](http://www.stelpro.com).



# TECHNICAL SPECIFICATIONS

WITHOUT CONTROL	BUILT-IN THERMOSTAT	24 V CONTROL	POWER	VOLTAGE	FLOW	THROW DISTANCE	HEAT RISE	WEIGHT
CODE	CODE	CODE	WATTS	VOLTS	CFM	M FT.	°C °F	KG LB
SK0501	---	---	500	120	60	2.4 8	26 46	5 11
SK0508	---	---	500	208	60	2.4 8	26 46	5 11
SK0502	---	---	500/375	240/208	60	2.4 8	26 46	5 11
SK0503	SK0503T	SK0503C24	500	347	60	2.4 8	26 46	5 11
SK0751	---	---	750	120	60	2.4 8	42 75	5 11
SK0758	---	---	750	208	60	2.4 8	42 75	5 11
SK0752	---	---	750/560	240/208	60	2.4 8	42 75	5 11
SK0753	SK0753T	SK0753C24	750	347	60	2.4 8	42 75	5 11
SK1001	---	---	1000	120	60	2.4 8	54 97	5 11
SK1008	---	---	1000	208	60	2.4 8	54 97	5 11
SK1002	---	---	1000/750	240/208	60	2.4 8	54 97	5 11
SK1003	SK1003T	SK1003C24	1000	347	60	2.4 8	54 97	5 11
SK1251	---	---	1250	120	60	2.4 8	79 143	5 11
SK1258	---	---	1250	208	60	2.4 8	79 143	5 11
SK1252	---	---	1250/940	240/208	60	2.4 8	79 143	5 11
SK1253	SK1253T	SK1253C24	1250	347	60	2.4 8	79 143	5 11
SK1501	---	---	1500	120	60	2.4 8	102 184	5 11
SK1508	---	---	1500	208	60	2.4 8	102 184	5 11
SK1502	---	---	1500/1125	240/208	60	2.4 8	102 184	5 11
SK1503	SK1503T	SK1503C24	1500	347	60	2.4 8	102 184	5 11
---	---	---	2000	120	90	3.2 10'6"	109 196	5 11
---	---	---	2000	208	90	3.2 10'6"	109 196	5 11
SK2002	---	---	2000/1500	240/208	90	3.2 10'6"	109 196	5 11
SK2003	SK2003T	SK2003C24	2000	347	90	3.2 10'6"	109 196	5 11

Add W for white or SW for soft white (consult the optional colours chart or contact your Stelpro representative for all other colours).  
 Models also available in 277 V.  
 --- not available

## ACCESSORIES

PRODUCT	DESCRIPTION
SKT1*	tamper-proof built-in thermostat [120 V-347 V] (grille must be removed to access this type of thermostat)
SKTBA*	adapter for suspended ceiling (2 ft. x 2 ft.) – recessed or surface mounted with surface adapter (not included)
SKSA*	surface adapter (SK model)
FD60MCW70	60 minute wall timer [120 V-277 V]
SKRE153T*	built-in electronic low voltage relay c/w transformer 24 V [15 A @ 208 V-347 V]

\* Add W for white or SW for soft white.  
 \* Factory installed



## TECHNICAL DRAWINGS

