

# ST252NPFF – ST402NPFF

## ELECTRONIC THERMOSTAT FOR FAN HEATERS

NON-PROGRAMMABLE



2500 W

4000 W



### A WIND OF CHANGE!

Stelpro's all-new non-programmable electronic thermostats designed specifically for fan heaters let you make the most of your comfort thanks to advanced features such as "Boost" and "Lobby" modes. Harmonious design, superior technology and safe operation merge to ensure your comfort in all circumstances.

#### ENERGY SAVINGS UP TO 12%\*

#### ECO MODE

ONE-CLICK TEMPERATURE SETBACK

#### HEAT "BOOST" FEATURE

RAPID TEMPERATURE RISE

#### LOBBY MODE

COMPENSATES FOR FAST TEMPERATURE DROPS

#### SAFE DESIGN

SEALED HOUSING

#### S<sup>3</sup> MOUNTING PLATE

STURDY, SIMPLE AND SAFE INSTALLATION

#### COLOUR

- white

#### FINISH

- molded plastic

#### WATTAGE AND VOLTAGE

##### ST252NPFF

- 150 W to 1250 W @ 120 V
- 260 W to 2160 W @ 208 V
- 300 W to 2500 W @ 240 V

##### ST402NPFF

- 150 W to 2000 W @ 120 V
- 260 W to 3475 W @ 208 V
- 300 W to 4000 W @ 240 V

#### CONTROL

- three-wire connection
- compatible with forced-air units
- eco mode: One-click temperature setback
- maximum power when "boost" mode is activated (with a timer)
- display in Celsius or Fahrenheit

#### ACCURACY

- accurate ambient temperature control of  $\pm 0.5$  °C (1°F)
- CSA C828-19
- temperature sensing with thermistor

#### TEMPERATURE RANGE

- 5 to 30 °C (41 to 86 °F)

#### WARRANTY

- three years

\*independent study

## TECHNICAL SPECIFICATIONS

| PRODUCT   | WATTS       |                | VOLTAGE     | MAX. AMPERAGE | FREQUENCY |
|-----------|-------------|----------------|-------------|---------------|-----------|
|           | CODE        | MINIMUM        | MAXIMUM     | VOLTS         | AMPERES   |
| ST252NPFF | 150/260/300 | 1250/2160/2500 | 120/208/240 | 10.4          | 60        |
| ST402NPFF | 150/260/300 | 2000/3475/4000 | 120/208/240 | 16.7          | 60        |

DIMENSIONS ST252NPFF: 4,35 in. (110,5 mm) wide, 4,94 in. (125,5 mm) high and 1,38 in. (35 mm) deep  
 DIMENSIONS ST402NPFF: 4,94 in. (125,5 mm) wide, 4,94 in. (125,5 mm) high and 1,38 in. (35 mm) deep

**°STELPRO**

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at [www.stelpro.com](http://www.stelpro.com).

