## PRODUCT DATA SHEET



## S7500i


Technical Data

Casting material : AISI316 - DIN 1.4401 Surface treatment : "E.P." (Electro polished)

Note: Standard safety factor for working load

is 1/4 of breaking load.





Internal threaded ends with sunken hexago-

**PRODUCT - DATA** 

S7500i



S75001 Internal threaded ends with sunken hexagonal

| \$7500i<br>\$\$316 | SIZE M<br>(mm/inch) | ØD<br>(mm) | ØD<br>(inch) | ØD1<br>(mm) | ØD1<br>(inch) | L<br>(mm) | L<br>(inch) | Unit<br>weight<br>(kgs) | Unit<br>weight<br>(lb) | B.L.<br>(kgs) | B.L.<br>(lb) |
|--------------------|---------------------|------------|--------------|-------------|---------------|-----------|-------------|-------------------------|------------------------|---------------|--------------|
| 6750-0153          | M5                  | 8.0        | 0.31         | 12          | 0.47          | 30        | 1.18        | 0.01                    | 0.02                   | 600           | 1,320        |
| 6750-0163          | M6                  | 8.0        | 0.31         | 12          | 0.47          | 35        | 1.38        | 0.01                    | 0.02                   | 1,250         | 2,750        |
| 6750-0840          | M8                  | 10.0       | 0.39         | 14          | 0.55          | 40        | 1.57        | 0.01                    | 0.02                   | 1,600         | 3,520        |
| 6750-0045          | M10                 | 13.0       | 0.51         | 17          | 0.67          | 45        | 1.77        | 0.03                    | 0.07                   | 3,250         | 7,150        |
| 6750-0104          | 1/4"                | 7.8        | 0.31         | 12          | 0.47          | 32        | 1.26        | 0.01                    | 0.02                   | 1,250         | 2,750        |

100% RECYCLABLE