



CERAMIC COAT FOR PAINT KIT

NANO CERAMIC 9H+

WIZARDSPRODUCTS.COM • COMPLETE PRODUCT INFORMATION

FEATURES:

- ♦ High Solids SiO2 Quartz
- ♦ Antioxidant - Antistatic
- ♦ UV, Acid, Salt, Chemical and Scratch Resistant Above 9H
- ♦ Repels Dirt and Water
- ♦ Easy Cleaning



HOW TO USE:

- 1: Wash vehicle and if needed decontaminate surface with Wizards® Mystic Clay, a clay mitt or clay disk to remove bonded contaminants.
- 2: Machine polish paint to remove scratches and imperfections for paint correction. Nano Ceramic 9H+ will not restore faded paint or hide scratches; it will magnify color, add clear gloss, slickness and hydrophobic surface tension.
- 3: After scratch removal (surface correction), wipe and degrease with Wizards® Precoat Cleaner to remove polish residue and oils to enable chemical bonding of coating. Spray to flood area, wipe lightly in a back and forth motion with a folded microfiber cloth to remove oils and contaminants, flip cloth and wipe to dry. Repeat this step and replace cloths as necessary to leave a 100% decontaminated surface.
- 4: Pour about 10 drops of coating onto an applicator pad and spread a thin layer evenly across small panels at a time, making sure to cover area fully by overlapping and changing directions. A reasonable area to apply at a time is one door, one fender, half the hood etc. Apply in one direction (north to south), then switch direction (east to west) to make sure to cover area evenly.
- 5: Wait about 2 to 4 minutes for coating to flash; this time will vary with temperature and humidity. Do not walk away and allow to dry. After the allowed flash time, gently wipe to level with a new, folded, edgeless microfiber cloth (300 GSM or higher). Wipe over gently until uniform. Do not push hard to remove too much; you only want to level and leave a uniform gloss, inspecting for rainbow flashing, dry areas (high spots), missed spots, or any cloth marks. It is recommended to overlap areas when applying and blend (when wiping to level) by using very light circular motions, bringing the new area into the previously applied drying area.
- 6: Second coat (recommended) after one hour dry time. Keep from water for 12 hours; full cure in 8 days.

PART NUMBERS & SIZES



Ceramic Coat for Paint (Nano Ceramic 9H+) - Part No. 31001

1.7 fl. oz. - 50 ml., 6/Case - Net Wt. 3 lbs.
Ceramic coating is an SiO2 infused polymer which is applied by hand to the exterior of your car creating a layer of protection.



Precoat Cleaner (Coating Prep) - Part No. 32031

4 oz. 12/Case - Net Wt. 4 lbs.
Surface preparation step required to remove all contaminants, prior to applying any WIZARDS® CERAMIC COATING.



Ceramic Detailer (SiO2 Infused Polymer Coating) - Part No. 51018

8 fl. oz. - 237 ml., 12/Case - Net Wt. 8 lbs.
WIZARDS SELECT® HYBRID CERAMIC DETAILER quickly brings your finish to a high gloss while enhancing surface protection.



Wizards Applicator Pads (2 Pad Set) - Part No. 36012

2 Pad Set, Size: 3.5" x 4.75"
Soft microfiber provides safe and even application of coatings on all panels and style lines, providing faster and more versatile application.



4 Edgeless Microfiber Cloths - Part No. 36324 (24 Pack)

300 GSM, 16" x 16" (40x40cm) Available Separately
Soft Microfiber cloths are edgeless, streak free, scratch free and super absorbent with no sewn border and have no tags or labels.

DETAILING • CLEANING • PROTECTION

DESCRIPTION:

WIZARDS® CERAMIC COAT FOR PAINT is extremely durable and weather resistant. It protects your paint/clear to shield against scratching, marring and road salt. Nano Ceramic 9H+ adds a new additional layer over your clear for an ultimate barrier.



WizardsProducts.com