



Select Pro Ultra Fine Machine Finish 3

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 12/21/2021

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Select Pro Ultra Fine 3
Product form : Mixture
Product Codes : 41003, 42003, 43003

1.2. Relevant identified uses of the substance or mixture and uses advised against

Buffing compound for paint

1.3. Details of the supplier of the safety data sheet

RJ Star, Inc. dba Wizards Products
11469 8th St. NE
Hanover, MN 55341

1.4. Emergency telephone number

Emergency number : 763-497-5155

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Combustible H227
Asp. Tox. 2 H305
Skin Irrit. 2 H315
Eye Irrit. 2B H320

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H227 - Combustible liquid
H305 - May be harmful if swallowed and enters airways
H315 - Causes skin irritation
H320 - Causes eye irritation

Precautionary statements (GHS-US) :

P210 - Keep away from flames and hot surfaces - no smoking
P264 - Wash skin thoroughly after handling
P280 - Wear eye protection, face protection, protective clothing, protective gloves
P301+P310 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER
P302+P352 - If on skin: Wash with plenty of soap and water
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P331 - Do NOT induce vomiting
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P370+P378 - In case of fire: Use water fog, foam, dry chemical or CO2 to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up
P501 - Dispose of contents and container in accordance with local regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

Select Pro Ultra Fine Machine Finish 3

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % |
|---|---------------------|---------|
| Naphtha, petroleum, hydrotreated heavy | (CAS No) 64742-48-9 | 10 - 17 |
| Petroleum distillates, hydrotreated light | (CAS No) 64742-47-8 | 2 - 7 |
| Aluminum oxide | (CAS No) 1344-28-1 | 15 - 25 |
| Other ingredients below reportable levels | | 57 - 75 |

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May be harmful if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation
- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways.
- Chronic symptoms : N/A

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Carbon dioxide. Dry powder. Water spray. Sand.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Product is not flammable.
- Explosion hazard : Product is not explosive.
- Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

- Precautionary measures fire : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

6.1.1. For non-emergency personnel

- Protective equipment : Wear Protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

Select Pro Ultra Fine Machine Finish 3

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Sweep or shovel spills into appropriate container for disposal. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

See Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Handle in accordance with good industrial hygiene and safety procedures. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Avoid breathing vapours, mist. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry, cool and well-ventilated place. Keep the container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Naphtha, petroleum, hydrotreated heavy (64742-48-9) | |
|---|-------------------------|
| Remark (ACGIH) | OELs not established |
| Remark (OSHA) | OELs not established |
| Aluminum oxide (1344-28-1) | |
| Remark (ACGIH) | OELs not established |
| OSHA PEL (TWA) (mg/m ³) | 5 (respirable fraction) |

8.2. Exposure controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment : Gloves. Protective goggles. Insufficient ventilation: wear respiratory protection.



Hand protection : Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection : Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection : Wear long sleeves

Respiratory protection : Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Viscous Liquid

Color : White

Select Pro Ultra Fine Machine Finish 3

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|--|---|
| Odor | : Pleasant scent |
| Odor Threshold | : No data available |
| pH | : 7.5 |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : 32 F |
| Boiling point | : >212 F |
| Flash point | : >190 F ISO 2719 Pensky-Martens Closed Cup |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapour pressure | : No data available |
| Relative vapour density at 20 °C | : No data available |
| Relative density (Specific gravity) | : 1.01 |
| Solubility | : Negligible in water |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : 8,000 – 11,000 cps |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Minimally toxic

| Naphtha, petroleum, hydrotreated heavy (64742-48-9) | |
|--|--------------|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 3160 mg/kg |

| Aluminum oxide (1344-28-1) | |
|-----------------------------------|--------------|
| LD50 oral rat | > 5000 mg/kg |

| | |
|--|--|
| Reproductive toxicity | : Not classified |
| Specific target organ toxicity (single exposure) | : Not expected to cause organ damage from a single exposure. |
| Specific target organ toxicity (repeated exposure) | : Not expected to cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | : May be harmful if swallowed and enters airways. |
| Symptoms/injuries after inhalation | : May cause respiratory irritation. |
| Symptoms/injuries after skin contact | : Causes skin irritation. |

Select Pro Ultra Fine Machine Finish 3

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after eye contact : Causes eye irritation.
Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways.
Chronic symptoms : None known.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No information available.

12.2. Persistence and degradability

Select Pro Ultra Fine Machine Finish 3

| | |
|-------------------------------|--------------------|
| Persistence and degradability | No data available. |
|-------------------------------|--------------------|

12.3. Bioaccumulative potential

Select Pro Ultra Fine Machine Finish 3

| | |
|---------------------------|---------------------------|
| Bioaccumulative potential | No information available. |
|---------------------------|---------------------------|

12.4. Mobility in soil

Select Pro Ultra Fine Machine Finish 3

| | |
|----------------|---------------------------|
| Ecology - soil | No information available. |
|----------------|---------------------------|

12.5. Other adverse effects

Other adverse effects : No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

In accordance with DOT

Not hazardous for transport

Additional information

Other information : No supplementary information available.

Transport by sea

Not hazardous for transport

Air transport

Not hazardous for transport

SECTION 15: Regulatory information

15.1. US Federal regulations

Select Pro Ultra Fine Machine Finish 3

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory

| | |
|-------------------------------------|--|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard Delayed (chronic) health hazard |
|-------------------------------------|--|

Aluminum oxide (1344-28-1)

| | |
|-----------------------|--|
| Section 302 (EHS) TPQ | |
|-----------------------|--|

| | |
|--------------------|--|
| Section 304 EHS RQ | |
|--------------------|--|

| | |
|-----------|--|
| CERCLA RQ | |
|-----------|--|

| | |
|-------------|-------------------------------|
| Section 313 | Listed on US SARA Section 313 |
|-------------|-------------------------------|

15.2. International regulations

No additional information available.

15.3. US State regulations

California Proposition 65

This product does not contain any chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

Select Pro Ultra Fine Machine Finish 3

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aluminum oxide (1344-28-1)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

SECTION 16: Other information

Indication of changes : Revision 1.0
Revision date : 12/21/2021
Other information : Author: KES.

NFPA health hazard : 1 - Can cause significant irritation.
NFPA fire hazard : 1 - Must be preheated before ignition can occur.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,
and are not reactive with water.



HMIS III Rating

Health : 1
Flammability : 1
Physical : 0
Personal Protection :

Volatile organic compounds (VOC): Approx. 163 grams/liter (1.36 lbs./gallon)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product