

# TINGLEY

est. 1896

## Steplite® X Powered by Bekina® Knee Boot

Style Number - 77253

Compliance Standards: ASTM F2413 M/IC EH\*



**Product Detail:** Made from polyurethane, a lightweight, foamed polymer, that demonstrates excellent abrasion-resistance, self-insulating properties, and outstanding ability to shed fats and oils. Composite safety toe does not transfer cold or set off metal detectors. Injection molded seamless construction provides 100% liquidproof protection. Soft and flexible upper, and fully lined interior for all day working comfort.

\*Electrical Hazard soles and heels are intended to reduce hazards due to accidental contact with live electrical circuits, electrically energized conductors, parts or apparatus. They are not intended for work environments where volatile chemicals or explosives may be present, where conductive footwear is required.

**Warning:** Electric Hazard features of the soles and heels will deteriorate in wet environments, and when worn with excessive wear on the soles and heels.

**Product Type:** Knee Boot

**Insole:** Removable, contour insole for superior comfort.

**Sizes:** US Men's 5 through 14

**Outsole Tread Pattern:** Self-cleaning, slip resistant, cleated outsole for superior grip on a variety of floor surfaces and conditions.

**Color:** Yellow Upper / Black Outsole

**Appearance:** Boots are clean and free from obvious defects, flash and contamination. The surfaces are visually consistent in texture and contrast with no evidence of foreign material or distortion. Molded products are fully formed, well defined and properly aligned, with level outsoles, smooth seams and neatly trimmed edges. Colors are consistent within and between lots.

**Material:** Polyurethane (PU)

**Closure Type:** None

**Labeling:** Lot code, country of origin, and size are marked on the outsoles. Printed hangtag displays name, style, size, UPC code, and product features and benefits. Boots are labeled to indicate compliance with ASTM F2413.

**Packaging:** Boots are pair packed in a clear plastic bag and labeled for individual sale. Packaged five (5) pairs per labeled, corrugated cardboard case.

**Applications:** Suited for various jobs within Food Processing, Dairy, Meats (Beef, Chicken, Pork), Farm/Ag and Petrochemical (Exploration and Drilling).

**Chemical Resistance:** Exceptional resistance to fats and oils, fuels, bleach, industrial salts, manure, mild acids and alkalis.

**Country of Origin:** Belgium

**Other:** Testing and certification documents are available upon request from Tingley Rubber Corporation.

Dims & Weight by Size:	M5 W7	M6 W8	M7 W9	M8 W10	M9 W11	M10 W12	M11 W13	12
Height (in.)	14.8	14.8	15.0	15.2	15.5	15.8	16.0	16.3
Ball Width (in.)	4.1	4.2	4.3	4.4	4.4	4.5	4.6	4.7
Heel-to-Toe (in.)	10.8	11.1	11.4	11.7	12.0	12.3	12.6	12.9
Topline Circumference (in.)	16.4	16.8	17.1	17.5	17.9	18.3	18.7	19.1
Weight (lbs)	3.1	3.2	3.4	3.5	3.7	3.8	4.0	4.1

Dims & Weight by Size:	13	14
Height (in.)	16.5	16.5
Ball Width (in.)	4.7	4.8
Heel-to-Toe (in.)	13.1	13.3
Topline Circumference (in.)	19.5	19.9
Weight (lbs)	4.3	4.4

**Case Pack:** 5 pairs

**Package Dimensions:**

		Case Carton (L x W x H)
Sizes 5 to 14		24 x 18 x 14 in

Steplite® X is a registered trademark of Bekina® Boots N.V.