


# TINGLEY

est. 1896

## Workbrutes® Steel Toe PVC Overshoe, Hi-Top

<b>Style Number - 35211</b>	<b>Compliance Standards:</b> ASTM F2413-05 M /I75/C75*
	<p><b>Product Detail:</b> Turns everyday shoes into on-the-job safety footwear. Workbrutes steel toe overshoes are an affordable solution for visitors or workers who require steel toe protection. Made to fit snug over most shoe styles, 100% waterproof seamless construction protects shoes from damage caused by site chemicals, contaminants, and wear. "ShoeLocks" molded into the vamp and above the heel counter along with left and right foot ensure a proper fit for a variety of footwear styles. Heavy-duty heel kick-off for hands free removal.</p> <p>*Tested and labeled as per ASTM F2413 - 2005 version. This version of the standard provided for testing and labeling the impact and compression resistance of the safety toe caps in overshoes.</p>
<b>Product Type:</b> Overshoe / Overboot	<b>Insole:</b> N/A
<b>Sizes:</b> Sizes Extra Small through XL (Fits US Men's shoes sizes 5 through 12.5)	<b>Outsole Tread Pattern:</b> Cleated Outsole: Spits out debris, providing excellent slip resistance. Wedge sole design is roomier to accommodate wider, thicker outsoles with either wedge or conventional heel construction.
<b>Color:</b> Black Upper /Yellow Outsole	<b>Appearance:</b> Overshoes are smooth in texture and contrast and free from obvious defects, flash and contamination with no evidence of foreign material or distortion. Products are fully formed, well defined and properly aligned with smooth seams neatly trimmed edges and a complete, uninterrupted top trim line. Material thickness in each overshoe is balanced to maximize wall consistency, minimize premature failure, and maintain overall functionality. Color consistency is maintained within and between lots.
<b>Material:</b> Specialty formulated PVC	
<b>Closure Type:</b> None	
<b>Labeling:</b> California Prop 65	<b>Packaging:</b> Overshoes are pair packed inside retail-ready folding carton. Packaged twelve (12) pairs per labeled, corrugated cardboard outer case.
<b>Applications:</b> Warehousing, Food Processing, Mining, Construction, General Industry, Transportation, Onsite Visitors, and Temporary Employees.	<b>Chemical Resistance:</b> Fats, oils, greases, alcohols, certain acids and alkalies, and certain hydrocarbons. Not recommended for use in ketones, aldehydes, and other aggressive solvents.
<b>Country of Origin:</b> Mexico	<b>Other:</b> Testing and certification documents are available upon request.

Dims & Weight by Size:	XS	SM	MD	LG	XL			
Height (in.)	4.0	4.0	4.1	4.3	4.5			
Ball Width (in.)	4.4	4.5	4.5	4.6	4.8			
Heel-to-Toe (in.)	11.0	11.5	12.0	12.7	13.5			
Topline Circumference (in.)	16.5	17.4	18.5	19.4	20.2			
Weight (lbs)								

Dims & Weight by Size:					
Height (in.)					
Ball Width (in.)					
Heel-to-Toe (in.)					
Topline Circumference (in.)					
Weight (lbs)					

<b>Case Pack:</b> 12 pairs		
<b>Package Dimensions:</b>		
	<b>Inner Carton (L x W x H)</b>	<b>Case Carton (L x W x H)</b>
XS	5.5 x 4 x 14 in.	17 x 16 x 15 in.
SM	5.5 x 4 x 14 in.	17 x 16 x 15 in.
MD	5.5 x 4 x 14 in.	17 x 16 x 15 in.
LG	5.5 x 4 x 14 in.	17 x 16 x 15 in.
XL	5.5 x 4 x 14 in.	17 x 16 x 15 in.
2X	5.5 x 4 x 14 in.	17 x 16 x 15 in.