


# TINGLEY

est. 1896

## Workbrutes G2® PVC Overshoe, 17 in. Ht

<b>Style Number - 45850 (Black / Black)</b> <b>45851 (Black / Red)</b>	<b>Compliance Standards:</b> N/A
	<b>Product Detail:</b> Workbrutes G2 are wider and have more room in the toe for ideal fit over safety toe work boots or other large shoes. Injection molded PVC provides seamless and 100% waterproof protection for your primary footwear. This 17 inch height, PVC overshoe features thicker, deeper cleats for better grip and longer wear than rubber overshoes and the Frigiflex® PVC compound contains special additives for high stretch and flexibility in cold temperatures. Expansion pleats in key entry areas for incredibly easy donning, even on heavy-duty work boots. Unique thumb pocket and texturing at the top opening allows firm, no-slip grip for easy donning. "ShoeLocks" molded into the heel counter help ensure a proper fit with a variety of footwear styles. Heavy duty heel kick-off for hands free removal.
<b>Product Type:</b> Overshoe / Overboot	<b>Insole:</b> N/A
<b>Sizes:</b> Sizes Extra Small through 2XL (Fits US Men's shoes sizes 5 through 17)	<b>Outsole Tread Pattern:</b> Cleated outsole spits out debris for excellent gripping action.
<b>Color:</b> Black Upper / Black Outsole (45850) Black Upper / Red Outsole (45851)	<b>Appearance:</b> Overshoes are smooth in texture and contrast and free from obvious defects, flash and contamination with no evidence of foreign material or distortion. Products are fully formed, well defined and properly aligned with smooth seams neatly trimmed edges and a complete, uninterrupted top trim line. Material thickness in each overshoe is balanced to maximize wall consistency, minimize premature failure, and maintain overall functionality. Color consistency is maintained within and between lots.
<b>Material:</b> Specialty formulated PVC	
<b>Closure Type:</b> Molded in button and two button holes. Non-metallic.	
<b>Labeling:</b> California Prop 65	<b>Packaging:</b> Overshoes are pair packed inside retail-ready folding cartons. Packaged six (6) pairs per labeled, corrugated cardboard outer case.
<b>Applications:</b> Food Processing, Construction, General Industry, Transportation, and certain Hazardous Waste Cleanup.	<b>Chemical Resistance:</b> Fats, oils, greases, alcohols, certain acids and alkalis, and certain hydrocarbons. Not recommended for use in ketones, aldehydes, and other aggressive solvents.
<b>Country of Origin:</b> China	<b>Other:</b> Testing and certification documents are available upon request.

Dims & Weight by Size:	XS	SM	MD	LG	XL	2X
Height (in.)	16.1	16.4	16.7	17.0	17.3	17.6
Ball Width (in.)	4.9	5.0	5.2	5.4	5.5	5.7
Heel-to-Toe (in.)	11.6	12.2	12.9	13.6	14.3	14.9
Topline Circumference (in.)	19.6	20.6	21.5	22.4	23.4	24.3
Weight (lbs)	4.6	5.0	5.4	5.9	6.2	6.4

Dims & Weight by Size:					
Height (in.)					
Ball Width (in.)					
Heel-to-Toe (in.)					
Topline Circumference (in.)					
Weight (lbs)					

<b>Case Pack:</b> 6 pairs		
<b>Package Dimensions:</b>		
	<b>Inner Carton (L x W x H)</b>	<b>Case Carton (L x W x H)</b>
XS	7 x 5 x 14 in.	16 x 15 x 15 in.
SM	7 x 5 x 14 in.	16 x 15 x 15 in.
MD	7 x 5 x 14 in.	16 x 15 x 15 in.
LG	7 x 6 x 16 in.	19 x 15 x 16 in.
XL	7 x 6 x 16 in.	19 x 15 x 16 in.
2X	7 x 6 x 16 in.	19 x 15 x 16 in.