



Safetyflex® Jacket

Stock Number - J41248



Compliance Standards: Flame resistant. Self extinguishing with flameout and afterglow less than or equal to 2 seconds after removal of ignition source and char length of less than 6 inches. Test Method ASTM D6413.

Garment Detail:

The jacket has raglan sleeve construction with a 90 degree sleeve-to-body angle, a storm fly front with hidden snap closure, an inner storm flap, hood snaps for detachable hood, and an elasticized inner cuff.

Garment Type: High performance rainwear, provides superior protection against acids, caustics, and chemicals.

Sizes: S, M, L, XL, 2X, 3X, 4X, 5X

Color: Green

Material: Green material is 13 oz./yd² Specialty PVC on 150D Polyester.

Seam Construction: All seams are RF/heat sealed and 100% waterproof.

Closure Type: Hidden snap closure with 4 snaps and storm fly.

Pockets:

Labels/Tags:
Label sealed to inside collar displays Tingley logo, size, Flame Resistance and country of origin. Care instructions, fabric composition, lot and date codes are located on the reverse.

Packaging: Printed polyethylene bag.

Other: Mildew Resistant.

Dimensions	S	M	L	XL	2X	3X	4X	5X
Chest	46"	50"	54"	58"	62"	66"	70"	74"
Length	29"	30"	31"	31"	32"	32"	32"	33"
Sleeve Length	34"	34"	34.5"	35"	35.5"	36"	36"	36"

Case Pack: 12 each

Case Dimensions/Weight

S = 15"(L) X 13"(W) X 13"(H) / 29 lbs.	2X = 15"(L) X 13"(W) X 13"(H) / 33 lbs.
M = 15"(L) X 13"(W) X 13"(H) / 30 lbs.	3X = 15"(L) X 13"(W) X 13"(H) / 35 lbs.
L = 15"(L) X 13"(W) X 13"(H) / 31 lbs.	4X = 15"(L) X 13"(W) X 13"(H) / 36 lbs.
XL = 15"(L) X 13"(W) X 13"(H) / 31 lbs.	5X = 15"(L) X 13"(W) X 13"(H) / 38 lbs.

Safetyflex® is a registered trademark of Tingley Rubber Corp.