		T		ìLE	Y			
		-	est. 1 DuraScri	<sup>896</sup>				
Stock Num	Compliance Standards: Flame resistant. Self extinguishing with   flameout and afterglow less than or equal to 2 seconds after removal of ignition source and char length of less than 6 inches.   Test Method ASTM D6413. Test Method ASTM D6413.							after
	degree sle	t has modifie	y angle, a s	sleeve const torm fly front				
Garment Type: Desig safety needs of custom extinguishing rainwear Sizes: S, M, L, XL, 2X	ners who req	uire durab						
Color: Yellow Material: Yellow material is 8 oz./yd <sup>2</sup> PVC on Polyester Scrim. Seam Construction: All seams are RF/heat sealed and 100% waterproof.				Labels/Tags: Label sealed to inside collar displays Tingley logo, size, Flame Resistance and country of origin. Care instructions, fabric composition, lot and date codes are located on the reverse.				
Closure Type: Snap c with 1 additional snap.	losure with 4	snaps and	d storm fly	Packaging	: Printed po	blyethylene b	oag.	
Pockets:				Other: Mildew Resistant.				
Dimensions	S	М	L	XL	2X	3X	4X	5X
Chest	45"	49"	53"	57"	61"	65"	69"	73"
Length	29"	30"	31"	31"	32"	32"	32"	33"
Sleeve Length	33.5"	34"	35"	35.5"	36"	36.5"	37"	37.5"
Case Pack: 12 each Case Dimensions/We S = 15"(L) X 13"(W) X	-	S.	2X = 15"(	_) X 13"(W)	X 9"(H) / 28	3 lbs.		
$M = 15"(L) \times 13"(W) \times L = 15"(L) \times 13"(W) \times XL = 15"(L) \times 13"(W) \times XL = 15"(L) \times 13"(W) \times 1$	9"(H) / 24 lb 9"(H) / 26 lbs	S. 3.	3X = 15"(1 4X = 15"(1	L) X 13"(W) L) X 13"(W) L) X 13"(W) L) X 13"(W)	X 9"(H) / 29 X 9"(H) / 31	) lbs. I lbs.		

DuraScrim™ is a trademark of Tingley Rubber Corp.