

## Flexible, durable, comfortable

Pylon® Metatarsal Guard Boots feature a floating metatarsal guard, steel safety toe, steel shank, Electrical Hazard (EH)\*rating, and excellent slip resistance for outstanding protection. 16" Ht. - Steel Safety Toe meets ASTM F2413 M/I/C.

- Floating metatarsal guard provides optimum flexibility and comfort and meets the ASTM F2413 Mt requirements.
- Meets ASTM F3445 Slip Resistance requirements.
- Electric Hazard (EH)\* rated.
- Steel shank for maximum arch support.
- Neoprene rubber provides a soft, flexible upper for optimum pliability and comfort and will outwear standard rubber boots in solvents, caustics, hydrocarbons, oils, fats, and acids.
- Long lasting Chevron outsoles offer abrasion resistance and provide excellent slip resistance on wet-contaminated or wet-clean surfaces.
- Snugleg last design hugs the foot for all day working
- Full length, durable sock liner feels great and helps to wick moisture.
- Removable polyurethane contour cushion insoles wick moisture and absorb shocks for maximum comfort.



**Exceptional slip resistance and protection from injury risks** such as dropped knives and heavy materials.



Chevron Outsole: Expels debris for slip resistance on wet contaminated surfaces.

**Ideal Applications:** Food Processing, (particularly Red Meat, Turkey and Dairy), Chemical and Petrochemical (Exploration, Production and Refineries).

Chemical Resistance: Animal fats and blood, oils, certain acids and alkalies, alcohols and more.



Test Method F2412







CHEMICAL







**PYLON METATARSAL GUARD BOOT** 

Maroon Upper - Metarsal Guard - Brown Chevron MB916B Outsole - Ht. 16" - Steel Safety Toe - EH Rated

\*Boot shall withstand 18,000 volts at 60 HZ for 1 minute with no current flow or leakage

6 - 15

Electrical Hazard soles and heels are intended to reduce the hazards due to accidental contact with live electrical circuits, electrically


current in excess of 1.0 milliamperes under dry conditions tested as per lab conditions in

energized conductors, parts, or apparatus Electric Hazard soles and heels are not intended for wear in those work environments where volatile chemicals or explosives may be present, where conductive footwear is





est. 1896











NGL EY