

TINGLEY

est. 1896

Safetyflex® Coverall

Stock Number - V41108



Compliance Standards: Flame resistant. Self extinguishing with flameout and afterglow less than or equal to 2 seconds after removal of ignition source and char length of less than 6 inches. Test Method ASTM D6413.

Garment Detail:

4-Piece coverall has tapered raglan sleeve construction with a 90 degree sleeve-to-body angle, take-up snaps on each leg cuff, a storm fly front with hidden snap and zipper closure, and an attached hood with a drawcord.

Garment Type: High performance rainwear, provides superior protection against acids, caustics, and chemicals.

Sizes: S, M, L, XL, 2X, 3X, 4X, 5X

Color: Green

Material: Green material is 13 oz./yd² Specialty PVC on 150D Polyester.

Seam Construction: All seams are RF/heat sealed and 100% waterproof.

Closure Type: Zipper closure with 4 hidden snaps and storm fly.

Pockets:

Labels/Tags:

Label sealed to inside collar displays Tingley logo, size, Flame Resistance and country of origin. Care instructions, fabric composition, lot and date codes are located on the reverse.

Packaging: Printed polyethylene bag.

Other: Mildew Resistant.

Dimensions	S	M	L	XL	2X	3X	4X	5X
Chest	46"	50"	54"	58"	62"	66"	70"	74"
Sleeve Length	34"	34"	34.5"	35"	35.5"	36"	36.5"	37"
Waist	42.5"	46"	50"	54"	58"	62"	66"	70"
Inseam	27.5"	28"	28.5"	29"	29.5"	30"	30.5"	31"

Case Pack: 12 each

Case Dimensions/Weight

S = 16"(L) X 12"(W) X 15"(H) / 32 lbs.

2X = 16"(L) X 12"(W) X 15"(H) / 38 lbs.

M = 16"(L) X 12"(W) X 15"(H) / 33 lbs.

3X = 16"(L) X 12"(W) X 15"(H) / 40 lbs.

L = 16"(L) X 12"(W) X 15"(H) / 35 lbs.

4X = 16"(L) X 12"(W) X 15"(H) / 42 lbs.

XL = 16"(L) X 12"(W) X 15"(H) / 37 lbs.

5X = 16"(L) X 12"(W) X 15"(H) / 44 lbs.

Safetyflex® is a registered trademark of Tingley Rubber Corp.