

TINGLEY

est. 1896

Class 2 FR Solid Breakaway Hook & Loop Vest

Stock Number - V81522



Compliance Standards: ANSI/ISEA 107 Type R, Class 2; ASTM F1506; NFPA 70E - CAT 1

Garment Detail: The vest has five breakaway points fastened with FR hook and loop strips. One breakaway point is located across each shoulder, one from the bottom of each sleeve opening to the base of the vest, and one at the front closure.

Garment Type: High visibility flame resistant 5-point breakaway vest

Reflective Tape: ANSI/ISEA 107 compliant 2" FR silver glass bead tape, heat sealed to garment.

Sizes: S-M, L-XL, 2X-3X, 4X-5X

Color: Fluorescent Yellow-Green

Configuration: Harness tape layout with one horizontal band.

Material: Fluorescent yellow-green material is 6.5 oz. 55% Modacrylic/45% Cotton blend.

Labels/Tags:

1. Size label with care instructions and ANSI 107, ASTM F1506, and NFPA 70E compliance statements.
2. Hangtag with stock #, size, and UPC code.
3. Disclaimer statement label.
4. Job Sight FR™ brand logo woven label with CAT rating.

Seam Construction: Stitched with 100% aramid thread.

Closure Type: FR Hook & Loop

Packaging: Polypropylene peggable, resealable bag.

Pockets: 2 Interior Pockets:

1. Interior lower right pocket - 7.0" x 8.5"
2. Interior upper left pocket - 5.5" x 6.0"

Other:

Arc rating: 6.8 cal/cm²

Dimensions	S - M	L - XL	2X - 3X	4X - 5X
Chest	50"	55"	60"	65"
Back Length	28"	28.5"	28.5"	29"

Case Pack: 50 each

Case Dimensions / Weight:

S-M = 19"(L) X 12"(W) X 18"(H) / 37 lbs

L-XL = 19"(L) X 12"(W) X 18"(H) / 40 lbs.

2X-3X = 19"(L) X 12"(W) X 23"(H) / 42 lbs.

4X-5X = 19"(L) X 12"(W) X 23"(H) / 44 lbs.

Job Sight FR™ is a trademark of Tingley Rubber Corp.