
## Dure Serim High Strength, Low Cost

## **DuraScrim**<sup>™</sup> Double Coated PVC On Polyester Suit Offers Durability At An Economy Price

Extremely high tear strength is the result of an open weave polyester scrim fabric being sandwiched between two layers of flame resistant PVC coating.

- Therm-O-Rad sealed seam construction for good chemical splash protection.
- Thicker outside coating for better abrasion resistance.
- Lighter interior coating protects fabric from chemical contamination.
- Flame resistant. Self extinguishing with flameout and afterglow less than or equal to 2 seconds after removal of ignition source. Test method ASTM D6413.

**Ideal Applications:** Light Chemical, Construction, Utilities, Agriculture, Food Processing, General Industry, and Hydroblasting.



DURASCRIM – 8 Oz. Mat'l Wt. – 10.5 Mil Thick				
JACKETS				
J56207	Yellow – Storm Fly Front – Hood Snaps	S – 3XL		
J56107	Yellow – Storm Fly Front –	S – 5XL		
	Attached Hood			
OVERALLS				
056007	Yellow – Plain Front	S – 3XL		
056107	Yellow – Snap Fly Front	S – 5XL		
SUIT				
S56307	Yellow – 3 Piece Suit – Jacket –	S – 5XL		
	Storm Fly Front – Detachable Hood –			
	Snap Fly Front Overall			
HOOD				
H56107	Yellow – Detachable	L		



FEATURES & BENEFITS	DURASCRIM
Full cut shoulder with 90° sleeve to body angle $\cdots\cdots$ for maximum freedom of movement	<b>X</b>
Therm-O-Rad sealed seams for 100% ·····waterproof protection	<b>X</b>
Storm fly front seals out wind, rain, and contaminants $\cdots\cdots$	<b>X</b>
Take-up snaps on sleeves and ankle cuffs for adjustable fit $\cdots$	<b>x</b>
Self material collar resists contamination · · · · · · · · · · · · · · · · · · ·	<b>X</b>
Non-conductive, non-corrosive hardware · · · · · · · · · · · · · · · · · · ·	<b>x</b>
Mildew resistant · · · · · · · · · · · · · · · · · · ·	<b>X</b>
Flame resistant tested*	<b>X</b>

Chemical Resistance: Many acids, oils, alcohols, salts, and alkalies.

\*Flame resistant. Self extinguishing with flameout and afterglow less than or equal to 2 seconds after removal of ignition source and char length less than 6 inches. (Test Method ASTM D6413).

DuraScrim<sup>™</sup> is a trademark of Tingley Rubber Corp.

expensive to offer the protection you need.