

Superior Shutters are fixed or adjustable aluminium shutters for interior and exterior applications. Shutters can be fixed, hinges, bifold or sliding with or without locks, bolts and flyscreen. The shutters can be used in a vertical or horizontal application. There are 3 series of shutters.

SHUTTER TYPE	1500 SERIES	2000 SERIES	2000 C5
Blade	Fixed	Adjustable	Adjustable Cyclone Rated
Blade Size			
90mm	✓	✓	✓
Standard Colours			
Pearl White Gloss (Interpon GA078A)	✓	✓	✓
White Birch (Cream) (Interpon GA057A)	✓	✓	✓
Black Satin (Interpon GN150A)	✓	✓	✓
Precious Silver Pearl (Dulux 7043K)	✓	✓	✓
Non-Standard Colours			
Western Red Cedar	✓	✓	✓
Custom Powder Coat	✓	✓	✓
Orientation			
Vertical	✓	✓	✓
Horizontal	✓	✓	✓
Installation Method			
Fixed in place	✓	✓	✓
Hinge	✓	✓	✓
Sliding	✓	✓	✓
Bifold	✓	✓	✓
Certification			
Wind rated to 280km/hr (3630 Pa)			✓
Wind rated to 180km/hr	✓	✓	
Warranty			
Finish 7 years*	✓	✓	✓
Fabrication 2 years	✓	✓	✓

*TERMS & CONDITIONS APPLY. NOT APPLICABLE TO CUSTOM POWDER COAT

PANEL INSTALLATION	MIN WIDTH	MAX WIDTH	MAX HEIGHT WITHOUT DIVIDER RAIL
Hinged Panel	250	1000	1800
Fixed in Place	250	1350	1800
Sliding	250	1350	1800
Bifold	250	700	1800
Series 2000 C5	250	1000	1800

APPLICATIONS

Screening for patios, decks, gazebos, internal & external windows and doors

MATERIAL SPECIFICATION

Aluminium 6063 T5 blades & channel

UV stabilised non-metal parts

Marine grade stainless steel tracking

Thermoset Powder-Coating - AKSO Nobel Powder 60UM

Superior Shutters 1500 Series are fixed blade screens with the blade set at 30° off vertical

ENGINEERING COMPLIANCE

Wind Load Testing to AS/NZS 1170.0-2002 and AS/NZS 1170.2-2002. The Superior Shutter C5 is able to withstand a pressure load of 3630 Pa which is equivalent to 280km/hr or a Max 4 / Min 5 Category cyclone.