

Ph 07 3277 2277

Fax 07 3277 2288

Email [sales@selectgear.com.au](mailto:sales@selectgear.com.au)

## NON-RETRACTABLE LAP SASH BELT

Non-retractable lap sash or static seat belts suit cross-body applications where it is not possible to mount a retractor. These include the rear and front RHS and LHS of many passenger vehicles. These belts are adjustable with the adjuster mechanism fitted adjacent to the top pillar anchor.

Standard belt length	2.6 metres
Long belt length	3.2 metres
Short belt length	2.0 metres

Buckles are either

Stalk (cable) mounted on the transmission tunnel (vertical surface)

Stalk (cable) mounted on the floor (horizontal surface) – note the anchor plate

Stem (steel plate) mounted on the seat or vertical bracket

Webbing Adjustable Standard (150mm - 610mm) Long (150mm – 950mm)

Buckles are measured in millimetres from the end of the buckle head (red release button) to the centre of the mounting hole of the anchor plate.

Buckle lengths available are

Stalk (tunnel mounted) – 220mm, 250mm, 300mm, 350mm, 400mm, 450mm

Stalk (floor mounted) – 250mm, 300mm, 350mm, 400mm. Right or Left

Stem (seat or vertical bracket mounted) – 100mm, 135mm, 170mm, 210mm

