

# 16AWG/2C Stranded Riser (CMR) Direct Burial Audio Cable

Product Specification

## Cable Detail



## Approval



## Description

- 16/2 Stranded CMR/CL3R Direct Burial Sound Audio Cable

## Applicable Standards

- For Communication and Signal Control Systems
- 2 Oxygen Free Bare Copper Conductors in an Overall Jacket

## Physical Characteristics

Conductor	Oxygen Free B.C.
Number of Conductor	2
AWG	16
Stranding	65
Diameter	0.0063 (inches)
<b>Insulation Material</b>	<b>PVC</b>
Diameter	0.0827 (inches)
Nominal Wall	0.0098 (inches)
<b>Jacket Material</b>	<b>FR-PVC</b>
Overall Diameter	0.2008 (inches)
Nominal Thickness	0.0197 (inches)
<b>Paper Tape</b>	<b>YES</b>
<b>Rip Cord</b>	<b>YES</b>
<b>Conductor Resistance</b>	<b>15.8 (ohms/1000m)</b>
<b>Voltage</b>	<b>300 (volts)</b>
<b>Nominal Weight</b>	<b>16 (pounds)</b>
<b>Temperature Rating</b>	<b>-20°C - 70°C</b>

## Colors

- Insulation Color  
Black / Red
- Jacket Color  
Black

## Part Number

203602BK

## Package

500FT / REELEX II

## Cable Marking

AUDIO CABLE 2 COND 16 AWG HI-STRAND OXYGEN FREE COPPER CMR/CL3R DIRECT BURIAL AUDIO CABLE SUN RES EXXXXXX C(ETL)US \*\*\*FT