


16AWG/2C OFC Stranded Direct Burial Cable

Cable Detail



Approval

- CL2/CL3 APPROVAL

Applicable Standards

- Multi-conductor-audio/sound, control, instrumentation & LED lighting cables

Physical Characteristics

vConstruction	
2 core	Oxygen Free Copper Wire Strands
AWG	16 / 1.307mm.sq
Stranding (wire NO/wire dia.mm)	65 / 0.16
Binding Tape	Paper Tape
Coverage (%)	+/- 125%
Material	PVC
Thickness (mm)	0.3
Insulation Diameter (mm)	2.2 +/- 0.2mm
Rip Cord	
Material	Nylon (210D)
Jacket	
Material	Glossy PVC
Nominal Thickness (mm)	0.89 +/- 0.15
Cable Dia. (mm)	6.2 +/- 0.3

Colors

- Insulation Color
Black / Red
- Jacket Color
Black, White

Part Number

203603BK
203603WT

Package

500FT / REELEX II

Cable Marking

16-2HFX AUDIO CABLE DIRECT BURIAL EXXXXXX (UL)
CL3 C(UL) CM 16AWG 2C (ROHS) OXYGEN FREE COPPER
ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***FT