

16AWG/4C OFC Stranded Riser (CMR) Audio Cable



Product Specification

Cable Detail



Approval



Description

- 16/4 Stranded CMR/CL3R Sound Audio Cable

Applicable Standards

- For Communication and Signal Control Systems
- 4 Oxygen Free Bare Copper Conductors in an Overall Jacket

Physical Characteristics

Conductor	Oxygen Free B.C.
Number of Conductor	4
AWG	16
Stranding	65
Diameter	0.0063 (inches)
Insulation Material	PVC
Diameter	0.0827 (inches)
Average Thickness	0.0122 (inches)
Min. Point Thickness	0.0106 (inches)
Assembly Diameter	0.2008 (inches)
Jacket Material	PVC
Outer Diameter	0.248 (inches)
Average Thickness	0.0236 (inches)
Min. Point Thickness	0.0213 (inches)
Rip Cord	Nylon
Conductor Resistance	15.5 (ohms)
Nominal Weight	27 (pounds)

Colors

- Insulation Color
Black / Red / White / Green
- Jacket Color
Black, White

Part Number

203702WT
203702BK

Package

500FT / REELEX II

Cable Marking

AUDIO CABLE 4 COND 16AWG HI-STRAND OFC
CMR/CL3R FT4 75C EXXXXXX C(ETL)US ***FT