

16AWG/4C Stranded Direct Burial Audio Cable



Product Specification

Cable Detail



Approval

- CL2/CL3 APPROVAL

Applicable Standards

- Multi-conductor-audio/sound, control, instrumentation & LED lighting cables

Physical Characteristics

Construction	
4 core	Oxygen Free Copper Wire Strands
AWG	16 / 1.307mm.sq
Stranding (wire NO/wire dia.mm)	65 / 0.16
Insulation	
Binding Tape	Paper Tape
Coverage (%)	+/- 125%
Thickness (mm)	0.3
Insulation Diameter (mm)	2.2 +/- 0.2mm
Rip Cord	
Material	Nylon (210D)
Jacket	
Material	Glossy PVC
Nominal Thickness (mm)	0.90 +/- 0.15
Cable Dia. (mm)	7.3 +/- 0.3
Insulation resistance	≥ 200MΩ / KM

Colors

- Insulation Color
Black / Red / White / Green
- Jacket Color
Black, White

Part Number

203703

Package

500FT / REELEX II

Cable Marking

16-4HFX AUDIO CABLE DIRECT BURIAL EXXXXXX (UL)
CL3 C(UL) CM 16AWG 4C (ROHS) OXYGEN FREE COPPER
ZONE/DEVICE A B C D E 1 2 3 4 6 7 8 9 ***FT