

14AWG/4C Stranded UV Rated Direct Burial Audio Cable

Cable Detail



Approval

- CM CL2/CL3 APPROVAL

Applicable Standards

- Multi-conductor-audio/sound, control, instrumentation & LED lighting cables

Physical Characteristics

Construction	
4 core	Oxygen Free Copper Wire Strands
AWG	14 / 2.11mm.sq
Stranding (wire NO/wire dia.mm)	105 / 0.16
Insulation	
Binding Tape	Paper Tape
Coverage (%)	+/- 125%
Thickness (mm)	0.4
Insulation Diameter (mm)	2.7 +/- 0.2mm
Rip Cord	
Material	Nylon (210D)
Jacket	
Material	Glossy PVC
Nominal Thickness (mm)	0.88 +/- 0.2
Cable Dia. (mm)	8.4 +/- 0.3

Colors

- Insulation Color
Black / Red, White / Green
- Jacket Color
Black

Part Number

203715

Package

500FT / REELEX II

Cable Marking

14-4HFX AUDIO CABLE DIRECT BURIAL EXXXXXX (UL)
CL3 C(UL) CM 14AWG 4C (ROHS) OXYGEN FREE COPPER
ZONE/DEVICE A B C D E 1 2 3 4 6 7 8 9 ***FT