

14AWG/2C OFC Stranded Riser (CMR) Audio Cable

Cable Detail



Approval



Description

- 14/2 Stranded CMR/CL3R Sound Audio Cable

Applicable Standards

- For Communication and Signal Control Systems
- 2 Oxygen Free Bare Copper Conductors in an Overall Jacket

Physical Characteristics

| Conductor | Oxygen Free B.C. |
|-----------------------------|---------------------|
| Number of Conductor | 2 |
| AWG | 12 |
| Stranding | 105 |
| Diameter | 0.0063 (inches) |
| Insulation Material | PVC |
| Diameter | 0.1023 (inches) |
| Average Thickness | 0.014 (inches) |
| Min. Point Thickness | 0.013 (inches) |
| Assembly Diameter | 0.2047 (inches) |
| Jacket Material | PVC |
| Outer Diameter | 0.2519 (inches) |
| Average Thickness | 0.0236 (inches) |
| Min. Point Thickness | 0.02126 (inches) |
| Rip Cord | Nylon |
| Conductor Resistance | 9.2 (ohms) |
| Nominal Weight | 22 (pounds) |
| Voltage Rating | 300V (volts) |

Colors

- Insulation Color
Black / Red
- Jacket Color
Black, White

Part Number

203716BK
203716WT

Package

500FT / REELEX II

Cable Marking

AUDIO CABLE 2 COND 14AWG HI-STRAND OFC
CMR/CL3R FT4 75C EXXXXXX C(ETL)US ***FT