


14AWG/2C Stranded UV Rated Direct Burial Audio Cable

Cable Detail



Approval

- CM CL2/CL3 APPROVAL

Applicable Standards

- Multi-conductor-audio/sound, control, instrumentation & LED lighting cables

Physical Characteristics

Construction	
2 core	Oxygen Free Copper Wire Strands
AWG	14 / 2.11mm.sq
Stranding (wire NO/wire dia.mm)	105 / 0.16
Binding Tape	Paper Tape
Coverage (%)	+/- 125%
Insulation	
Material	PVC
Thickness (mm)	0.4
Insulation Diameter (mm)	2.7 +/- 0.15mm
Rip Cord	
Material	Nylon (210D)
Jacket	
Material	Glossy PVC
Nominal Thickness (mm)	0.84 +/- 0.1
Cable Dia. (mm)	7.3 +/- 0.2

Colors

- Insulation Color
Black / Red
- Jacket Color
Black, White

Part Number

203718BK
203718WT

Package

500FT / REELEX II

Cable Marking

14-2HFx AUDIO CABLE DIRECT BURIAL EXXXXXX (UL)
CL3 C(UL) CM 14AWG 2C (ROHS) OXYGEN FREE COPPER
ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***FT