

14AWG/4C Stranded Riser (CMR) Audio Cable

Cable Detail



Approval



Description

- 14/4 Stranded CMR/CL3R Sound Audio Cable

Applicable Standards

- For Communication and Signal Control Systems
- 4 Oxygen Free Bare Copper Conductors in an Overall Jacket

Physical Characteristics

| Conductor | Oxygen Free B.C. |
|----------------------------|------------------|
| Number of Conductor | 4 |
| AWG | 14 |
| Stranding | 105 |
| Diameter | 0.0063 (inches) |
| Insulation Material | PVC |
| Diameter | 0.1023 (inches) |
| Average Thickness | 0.014 (inches) |
| Min. Point Thickness | 0.013 (inches) |
| Assembly Diameter | 0.248 (inches) |
| Jacket Material | PVC |
| Outer Diameter | 0.3149 (inches) |
| Average Thickness | 0.0315 (inches) |
| Min. Point Thickness | 0.0283 (inches) |
| Rip Cord | Nylon |
| Conductor Resistance | 9.2 (ohms) |
| Nominal Weight | 42 (pounds) |

Colors

- Insulation Color
Black / Red / White / Green
- Jacket Color
Black, White

Part Number

203720BK
 203720WT

Package

500FT / REELEX II

Cable Marking

AUDIO CABLE 4 COND 14AWG HI-STRAND OFC
 CMR/CL3R FT4 75C EXXXXXX C(ETL)US ***FT