

# Category 5E UTP CMP/Plenum Cable



## Category 5E UTP CMP/Plenum Cable

Category 5E cabling solution supports the operation of 1000 BASE-T over 100 meters and are qualified for frequency up to 350 MHz. It provides bandwidth required for multi-media, broadband video, analog video and other future applications.

### Standard Compliances

All proposed Category 5E requirements as per ANSI/TIA/EIA, ISO/IEC, and CENELEC EN Standards, ANSI/TIA-568-C.2 Category 5E ISO/IEC 11801 Class D+ 2nd Edition CENELEC EN 50173-1 IEC 61156-5, CENELEC EN 50288-3-1 for Horizontal Cable

Flame retardancy is verified according to NFPA 262

### Construction

Primaries: Conductor: 24 AWG (MIN.0.517mm) Solid Bare Copper Dual Insulation, Fep On All 4 Pairs

Pair Assembly: 2 Primaries Twisted In Varied Lays

Assembly: 4 Pairs Cabled Together, And 1 Rip Cord (Nylon Fiber)

Jacket: No Lead Plenum Rated Thermoplastic, Nominal Cable OD: Nominal: 6.0 mm

Listing: C(UL)US or C(ETL)US Type CMP UL or ETL Verified to Category 5E

### Physical Characteristics

Cable Weight: 13.87kg/1000ft (45.47 Kg/km)

Bending Radius: 1.9" (48mm) Min. (8×Cable OD)

Minimum Bend Radius: 8×Cable Diameter For 4-pair Unshielded Twisted-pair (UTP)

Horizontal Cable, Under No-load Conditions

Pulling Tension: 25 lbf (110 N) Max

Operating Temp.: -20°C To +60°C (-4°F to +140°F)

Storage Temp.: -20°C To +75°C (-4°F to +167°F)

Installation Temp.: 0°C To +60°C (+32°F to +140°F)

### Electrical Properties

Operating Temp: -70°C ~ +150°C

Voltage: 300V/AC Or V/DC

Capacitance: 5.6nf/100m.Nom

Characteristic Impedance: 100±15% Ohms, 1 - 250Mhz

velocity of Propagation: 69% Nom.

DCR: Conductor: 9.38 Ohms/100m.Nom

D-C Resistance Unbalance: 5%, Max.

Propagation Delay: 250mhz 536ns/100m Max.

Delay Skew: 45ns/100m.MAX

### Application

1000BASE-T Gigabit Ethernet, 100BASE-T Fast Ethernet (IEEE 802.3), 10BASE-T

100 VG - AnyLAN(IEEE802.12), 155/622 Mbps ATM, 350MHz Broadband Video

Voice, T1, ISDN

### Ordering Information

**100955XX** Cat.5E UTP 24AWG CMP/Plenum Cable, 1000ft(UL)

XX=BK(Black) BL(Blue) GN (Green) GY(Gray) OR(Orange) RD(Red) PU(Purple) WT(White)

YW(Yellow) IV(Ivory)

### Electrical Performance

Freq (MHz)	Attenuation (dB)		NEXT (dB/100m)		PS NEXT (dB)		ACR (dB)		ACR-F (dB)		PSACR-F (dB)		Return Loss (dB)	
	Nor.	Typ.	Nor.	Typ.	Nor.	Typ.	Nor.	Typ.	Nor.	Typ.	Nor.	Typ.	Nor.	Typ.
1.0	2.0	1.8	65.3	77.7	62.3	75.2	63.3	75.9	63.8	69.2	60.8	68.5	20.0	40.1
4.0	4.1	3.7	56.3	68.7	53.3	66.0	52.2	65.0	51.7	57.5	48.7	57.0	23.0	40.1
10.0	6.5	6.0	50.3	60.7	47.3	58.3	43.8	54.7	43.8	49.0	40.8	48.2	25.0	37.3
16.0	8.2	7.7	47.3	56.1	44.3	53.7	39.1	48.4	39.7	45.6	36.7	43.8	25.0	36.7
20.0	9.3	8.6	45.8	55.3	42.8	52.9	36.5	46.7	37.7	43.6	34.7	42.8	25.0	36.0
31.25	11.7	10.8	42.9	52.7	39.9	50.0	31.2	41.9	33.9	40.1	30.9	39.3	23.6	32.6
62.5	17.0	15.5	38.4	48.0	35.4	45.5	21.4	32.5	27.8	34.7	24.8	33.5	21.5	31.6
100.0	22.0	19.8	35.3	44.5	32.3	42.2	13.3	24.7	23.8	30.4	20.8	29.4	20.1	31.7
125.0	24.8	23.0	33.9	43.0	30.9	41.4	9.1	13.4	21.9	25.9	18.9	26.3	19.5	27.8
200.0	32.4	31.4	30.8	39.5	27.8	38.0	-	8.10	17.8	20.0	14.8	19.2	18.0	24.8
250.0	36.8	36.0	29.4	37.5	26.4	37.0	-	1.50	15.9	18.1	12.9	15.1	17.4	22.2
300.0	40.8	41.0	28.4	29.5	25.4	34.1	-	1.50	15.9	17.1	12.9	13.1	16.8	21.8
350.0	44.9	43.0	27.1	28.5	24.1	30.1	-	1.40	13.9	15.1	11.9	12.1	16.3	20.3

