



| 8806 |   |    |              |
|------|---|----|--------------|
| P1   |   | P2 |              |
| 1    | ↔ | 1  | WHITE/ORANGE |
| 2    | ↔ | 2  | ORANGE       |
| 3    | ↔ | 3  | WHITE/GREEN  |
| 6    | ↔ | 6  | GREEN        |
| 4    | ↔ | 4  | BLUE         |
| 5    | ↔ | 5  | WHITE/BLUE   |
| 7    | ↔ | 7  | WHITE/BROWN  |
| 8    | ↔ | 8  | BROWN        |

NOTE: All relevant materials are complied with RoHS directive .

| 3   | MOLDED PVC <b>GRAY TO PURPLE</b>   | H1BP01-0304U07 |          | M304     |
|-----|--|----------------|----------|----------|
| 2   | 4 TWISTED PAIRS CAT.6A 24AWG STRAND UTP WITH CROSS, OD6.9mm, JACKET GROOVE <b>GRAY TO PURPLE</b> | H5AJ19-0304U07 | (L+20)mm | M304     |
| 1   | 8P8C MODULAR PLUG (P8-040-1), GOLD PLATING 50u" ON CONTACTS, TRIPLEX                             | A1ND19-0205    | 2        | M205     |
| No. | DESCRIPTION  |                | Q'TY     | Supplier |

|          |       |  |  |
|----------|-------|--|--|
| APPROVED |       |  | Cable Length Unless Other Spec.<br>Tolerances:<br>0 ~200mm ±10mm<br>201~1000mm ±20mm<br>1001 ~1500mm ±25mm<br>1501~2100mm ±30mm<br>2100mm↑ ±40mm |
| CHECKED  | HU    |  |  |
| DRAWING  | JIANG |  |  |