


Transceiver Module

Spec Sheet

10Gbps SFP+ Module Transceiver

CTPD-SFP-10-SR



Application: 10GBase-SR/SW 10G Ethernet

Description

The CTPD-SFP-10-SR is a 10Gbps enhanced small form factor pluggable SFP+ transceiver compatible with 10GBASE-SR/SW. It is suitable for multi-mode fiber (MMF) communications in 10Gbps Ethernet.

Product Features

- | Up to 10Gbps data links
- | 300m with 50/125µm 2000MHz MMF
- | 850nm VCSEL laser
- | Duplex LC Connector
- | Hot-pluggable SFP+ footprint
- | Single 3.3V power supply Applications
- | Operating temperature: -5°C to 85°C
- | RoHS
- | Digital Diagnostic Monitor (DDM)
- | Power Consumption < 0.8W

Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Unit
Supply Voltage	V_{CC}	-0.5	4	V
Storage Temperature	T_s	-40	85	°C
Operating Case Temperature	T_C	-5	85	°C

Recommended Operating Environment

Parameter	Symbol	Min.	Typical	Max.	Unit
Operating Case Temperature	T_C	-5		85	°C
Power Supply Voltage	V_{CC}	3.15	3.3	3.45	V
Power Supply Current	I_{CC}			200	mA
Data Rate			10		GBps
Max Link Length on 50/125µm 2000MHz MMF	L_{max}			300	m

Optical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Unit
Transmitter					
Centre Wavelength	λ_C	840	850	860	nm
Spectral Width (RMS)	Σ			0.5	nm
Average Output Power	P_{out}	-5		-1	dBm
Extinction Ratio	ER	3.5			dB
Average Launch Power of Off Transmitter	P_{off}			-30	dBm
Receiver					
Centre Wavelength	λ_C	840		860	nm
Receiver Sensitivity	P_{IN}			-13	dBm
Receiver Overload	P_{max}	0.5			dBm
LOS De-Assert	LOS_D			-18	dBm
LOS Assert	LOS_A	-30			dBm
LOS Hysteresis		0.5			dB

Electrical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Unit
Transmitter					
Input Differential Impedance	Z_{in}	90	100	110	Ω
Data Input Swing Differential	V_{in}	200		700	mV
Tx-Dis Disable	V_d	2.0		V_{CC}	V
Tx-Dis Enable	V_{en}	0		0.8	V
Receiver					
Data Output Swing Differential	V_{out}	300		800	mV
Rx-Los Fault	V_{lf}	2.0		V_{CCHOST}	V
Rx-Los Normal	V_{ln}	0		0+0.8	V
Output rise and fall time	T_r, T_f	28			ps

EEPROM Serial ID Memory Contents

Add.	Size (Bytes)	Name of Field	Hex	Description
BASE ID FIELDS				
0	1	Identifier	03	SFP
1	1	Ext. Identifier	04	SFP function is defined by serial ID only
2	1	Connector	07	LC
3-10	8	Transceiver	10 00 00 00 00 00 00 00	Transmitter Code
11	1	Encoding	06	64B/66B
12	1	BR, Nominal	67	10.3Gbps
13	1	Reserved	00	
14	1	Length (9um) km	00	80m 20m
15	1	Length (9um) km	00	
16	1	OM2 Length (50um) m	08	
17	1	OM1 Length (62.5um) m	02	
18	1	Length (Copper)	00	
19	1	OM3 Length (50um) m	1E	30m
20-35	16	Vendor Name	43 2D 4C 49 47 48 54 20 20 20 20 20 20 20 20 20	C-LIGHT * OEM available
36	1	Reserved	00	
37-39	3	Vendor OUI	00 00 00	* OEM available
40-55	16	Vendor PN	xx xx xx xx xx xx xx xx xx xx xx xx xx xx xx xx	* OEM available
56-59	4	Vendor Rev	30 31 20 20	01
60-61	2	Wavelength	03 52	850nm
62	1	Reserved	00	
63	1	CC_BASE	xx	Check Code for Base ID Field
EXTENDED ID FIELDS				
64-65	2	Options	00 1A	Loss/ TX_Fault/ TX_Disable
66	1	BR, Max	00	
67	1	BR, Min	00	
68-83	16	Vendor SN	43 4C xx xx xx xx xx xx xx xx xx 20 20 20 20 20	SN of Transceiver (ASCII). Exp. "HDXXXXXXXXXX"
84-91	8	Date Code	xx xx xx xx xx xx 20 20	YY/MM/DD Exp. 120727
92	1	Diagnostic Monitoring	68	
93	1	Enhanced Options	80	
94	1	SFF_8472 Compliance	03	
95	1	CC_EXT	Check sum	Check sum for Extended ID
VENDOR SPECIFIC ID FIELDS				
96-127	32	Vendor Specific	20 20 20.....	Depends on Customer Info
128-255	128	Reserved	FF FF FF.....	Depends on Customer Info

DDM THRESHOLD

	Low Alarm	Low Warn	High Warn	High Alarm
Temperature	-13°C	-8°C	88°C	93°C
Voltage	2.9V	3V	3.6V	3.7V
Tx Bias	4mA	5mA	10.8mA	11.8mA
Tx Power	-6dBm	-5dBm	-1dBm	0dBm
Rx Power	-16dBm	-14dBm	-1dBm	0dBm

Pin Definitions




Diagram of Host Board Connector Block Pin Numbers and Names


Pin	Signal Name	Description	Ref.
1	VEET	Transmitter Ground (Common with Receiver Ground)	7.1
2	TFAULT	Transmitter Fault. Not supported.	
3	TDIS	Transmitter Disable. Laser output disabled on high or open.	7.2
4	MOD_DEF (2)	Module Definition 2. Data line for Serial ID.	7.3
5	MOD_DEF (1)	Module Definition 1. Clock line for Serial ID.	7.3
6	MOD_DEF (0)	Module Definition 0. Grounded within the module.	7.3
7	RS0	Rate Select0, optionally controls SFP+ module receiver. When high input signaling rate > 4.25GBd and when low input signaling rate < 4.25GBd	
8	LOS	Loss of Signal indication. Logic 0 indicates normal operation.	7.4
9	RS1	Rate Select1, optionally controls SFP+ module receiver. When high input signaling rate > 4.25GBd and when low input signaling rate < 4.25GBd	
10	VEER	Receiver Ground (Common with Transmitter Ground)	7.1
11	VEER	Receiver Ground (Common with Transmitter Ground)	7.1
12	RD-	Receiver Inverted DATA out. AC Coupled.	
13	RD+	Receiver Non-inverted DATA out. AC Coupled.	
14	VEER	Receiver Ground (Common with Transmitter Ground)	7.1
15	VCCR	Receiver Power Supply	
16	VCCT	Transmitter Power Supply	
17	VEET	Transmitter Ground (Common with Receiver Ground)	7.1
18	TD+	Transmitter Non-Inverted DATA in AC Coupled.	
19	TD-	Transmitter Inverted DATA in AC Coupled.	
20	VEET	Transmitter Ground (Common with Receiver Ground)	7.1

Notes:

- 7.1 Circuit ground is internally isolated from chassis ground.
- 7.2 Laser output disabled on TDIS > 2.0V or open, enabled on TDIS < 0.8V.
- 7.3 Should be pulled up with 4.7k - 10kohms on host board to a voltage between 2.0V and 3.6V. MOD_DEF (0) pulls line low to indicate module is plugged in.
- 7.4 LOS is open collector output. Should be pulled up with 4.7k - 10kohms on host board to a voltage between 2.0V and 3.6V. Logic 0 indicates normal operation; logic 1 indicates loss of signal.

Transceiver Module

Package Outline



Products List

Ethernet Series:

- PoE Switch (unmanaged or managed or industrial grade or outdoor rainproof)
- PoE Extender (indoor, outdoor waterproof and rainproof, industrial grade)
- PoE injector
- PoE splitter
- PoE/EOC converter
- Ethernet switch
- Wireless bridge
- etc.

Power Series:

- DC12V power box
- DC12V power adapter
- AC power adapter
- AC12V/24V power box
- AC-DC converter
- DC-DC converter
- 48V POE power adapter
- Switch Mode Power Supply
- Rack power supply
- etc.

OTHER:

- Video Balun (1080P, 4K, 8K)
- HDMI (split, switcher, extender, optic fiber cable)
- Cable (Network, HDMI, VGA, DC, DIY, HDIY, coaxial, twisted pair)
- Converter (BNC, DC, RCA, RJ45)
- Tools (RJ45, BNC...)
- Cabinet
- Fiber Module
- etc.