

22AWG/6C Stranded Shielded Riser (CMR) Security Cable

Cable Detail



Approval



Description

- 22/6 Shielded Stranded Bare Copper CMR Security Cable

Applicable Standards

- Class 2 Power Limited Circuit Cable and Communications
- Cable for General Purpose Application

Physical Characteristics

Conductor	Stranded Bare Copper
Number of Strands	7
Number of Conductor	6
AWG	22
Insulation Material	Polyvinyl Chloride (PVC)
Insulation Diameter	0.007" (mm)
Colors	Green / Red / Black / White / Brown / Blue
Shield	Low Smoke Aluminum Mylar
Drain Wire	24 AWG Tinned Copper
PE Tape	Yes
AL Foil Shield	Yes
Jacket Material	FR-(PVC)
Thickness	0.015" (0.38mm)
Nominal Outer Diameter	0.163" (4.14mm)
Rip Cord	Yes

Electrical Performance	
Rated Temperature	-20C to 75C
Voltage Rating	300V RMS
Nominal Weight	28 (pounds)

Colors

- Insulation Color
Green / Red / Black / White / Brown / Blue
- Jacket Color
White

Part Number

SEC-305WT

Package

1000FT / REELEX II

Cable Marking

22AWG 6 COND STRANDED SHIELDED XXXXXXXX CMR FT4 C(ETL)US ****FT