



CONNECTION

HDMI PLUG		HDMI PLUG
2		2
1	T.M.D.S Data 2+	1
3	T.M.D.S Data 2-	3
5		5
4	T.M.D.S Data 1+	4
6	T.M.D.S Data 1-	6
8		8
7	T.M.D.S Data 0+	7
9	T.M.D.S Data 0-	9
11		11
10	T.M.D.S Clock+	10
12	T.M.D.S Clock-	12
17		17
14	Utility / HEAC+	14
19	HPD / HEAC-	19
13	CED	13
15	SOL	15
16	SDA	16
18	+5V Power	18
Shell	Braid Shield	Shell

**PHYSICAL CHARACTERISTICS**

OPERATING TEMPERATURE RANGE : -24 TO 85°C

HUMIDITY : 10%~90%RH.

**ELECTRIC TESTING**

100% OPEN & SHORT TESTING.

INULATION RESISTANCE : ≥ 20 MΩ.

CONDUCTOR RESISTANCE : ≤ 3 Ω.

VOLTAGE : 300V DC/0.1S.

**RoHS**

Part #	1815xx Series	Part #	Cable Length (mm)
Title	High Speed HDMI Cable with Waterproof Hood and Cap Connector	3 Feet	915±50
		7 Feet	2135±50
Unit		10 Feet	3050±50
mm		15 Feet	4575±50

HOOD	PVC 50P, UL94V-0
DUSTPROOF CAP	PVC
O-RING	EPDM
MAIN BODY & DUST CAP	PBT+GF, UL94V-0