





71424D - LED BRONZE MEDIUM WALL PACK

277-480V 60W 5000K






Built-In Photocell Included!

FEATURES:

- Die Cast Aluminum Housing/ Stainless Hardware
- Polyester Bronze Powder Coating
- Aluminum Heat Sink & Customized Fin Design for Optimal Heat Dissipation
- Heat Resistant Optics
- Borosilicate Glass Lens
- 0-10V Dimmable
- Photocontrol included with on/off switch
- Operation Temperature: -40°F - 104°F
- Emergency Battery Backup (Sold Separately)
- Light Pattern: 110°
- Certifications: ETL/cETL
- DLC PRODUCT ID#: S-KSPOND
- Wet Location Rated
- 5 Year Warranty

| Part# | Housing Color | Wattage | Lumens | CCT | Voltage | Dimming | Replaces Metal Halide | DLC PRODUCT ID#: |
|--------|---------------|---------|--------|-------|----------|---------|-----------------------|------------------|
| 71424D | Bronze | 60W | 8042 | 5000K | 277-480V | 0-10V | 175W | S-KSPOND |

PHOTOMETRY:





71424D - LED BRONZE MEDIUM WALL PACK

277-480V 60W 5000K

TECHNICAL SPECIFICATIONS:

Electrical:

Input Voltage: 277-480V

Current: see chart pg 1

Frequency: 50/60Hz

Power Factor: $\geq .90$

THD: $< 20\%$ @120V

Product Parameters:

Efficacy: 140 lumens per watt

50,000+ Hour L70 Life Span

CCT: 5000K (Cool White)

Chromacity Measurements:

Beam Angle: 110°

BUG Rating: B1-U4-G5

CRI: 74

R9: -30

Component Specifications:

LED

277-480V

Dimming: 0-10V

Operating Temperature: -40°F - 104°F

Construction:

Housing: Die Cast Aluminum Alloy Powder Coated

Finish

Lens Material: Prismatic Borosilicate Glass Lens Lens:

UV Resistant Fire Resistant

Ingress Protection: WET location Rated

Mounting: Wall Mount

Listings:

cETLus

DLC PRODUCT ID#: S-KSPOND

Warranty:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal and proper usage).