



LL4SR

4" Square Regressed 2nd Gen Plenum LED 14.5W



Type IC, Air-Tight, Wet & Plenum

DESCRIPTION

4" Square Recessed LED With Integral Driver In Connection Box
Commercial Grade Quality With Architectural Design


FEATURES & BENEFITS

2" Deep - Install Where Ceiling Space Is Limited
Type IC Rated - No Housing Required
CRI 90+ for True Color Rendering
Fast & Easy To Install - Save On Labor
Driver Inside Connection Box - No Junction Box Needed
Armored Cable & Metal Connectors - Open Plenum Rated


MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips. Ceiling Clearance Required: 2"

DIMENSIONS: ID 4" OD 5" Sq Cut Out 4" to 4 1/4"



120V TRIAC Dimmable Driver Included



Optional 120V-347V Driver 0-10V Dimmable



Order Separately as [model # LLL-LD1535TR](#)

ORDERING GUIDE Example: **LL4SR - 30K - WH**

	CCT	Trim Finish	
LL4SR	- xxK	- xx	
2700K	27K	WH	White
3000K	30K	BK	Black
4000K	40K		
DTW 30K-18K	3018K	Dim to Warm 3000K to 1800K	

Project: _____

Location: _____

Model #: _____ Qty: _____

Notes: _____

SPECIFICATION

Applications	Recessed Ceiling Mount
Energy Used	14.5 W
Color Temperature (K)	2700 3000 4000 Dim to Warm 3000-1800K
Light Output (lm)	850 900 950 780
Halogen Equivalent	90 W
Beam Angle	90°
CRI	90 +
Default Driver Input	120V AC Triac Dimmable
Optional Driver Input	120V-347V AC 0-10V Dimmable
Junction Box Wire Capacity	Max 5 No 12 AWG or 8 No 14 AWG
Power Factor	0.98
Approved Location	Insulated Ceilings, Open Plenum, Wet
IP Rating	IP 54
Air Tight	Yes
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)
Projected Life	70% Light Output at 50,000 Hours
Certification	cULus, Energy Star (except DTW)
Warranty	10 Year Residential / 5 Year Commercial

AVAILABLE TRIMS



White



Black

ACCESSORIES

Sold Separately



Armored Low Voltage Extension FT6 / CMP rated [10ft model # MEC10](#)



[13" Mounting Plate Flat model # MP4-2](#)



[13" Mounting Plate Flanged model # MP4](#)



[26" Flat Rough-In Plates model # RIP4](#)



[Flanged Plate with Hanger Bars model # FRP4](#)

COMPLIANCE



**Type IC
Air-Tight
Open Plenum**

Lotus LED Lights USA

250 H Street # 301, Blaine WA 98230 tel 360-200-5500
Hainesport NJ, Naples FL, Dallas TX, Vancouver WA

www.LotusLEDLights.com

mailing addresses
warehouses

Lotus LED Lights CANADA

702 Chester Rd, Delta BC V3M 6J1 tel 604-538-3090
Delta BC & Mississauga ON