



32W T8 850K 48 MED BI-PIN
Item #528832
Ordering Code F32T8/850/EW
UPC 739698528823

- High performance tri-phosphor for maximum brightness and color rendering
- Can be used on both instant and rapid start ballasts
- Reduced wattage F28 and High Lumen F32 CEE qualified
- Reduced wattage 38W T8s produce equal light output while using less energy than standard 32W T8s
- High Lumen T8s are up to 20% more efficient than standard 32W T8s
- This item contains mercury. It cannot be shipped into the state of Vermont (VT) or Maine (ME) due to non-compliance with recycling regulations in these states. If you reside in any state not listed you can ignore this warning.



TECHNICAL SPECIFICATIONS

| | | | | | | | |
|---------------------|-------|--------------------|--------------|--------------------|--------------------|-----------------|-------------------------|
| Item # | Watts | Bulb Type | Base | Volts | Finish/Description | Beam Angle (°) | Color Temperature (CCT) |
| 528832 | 32 | T8 | BI-PIN | N/A | Frost | N/A | 5000K |
| Color | CRI | Lumens | CBCP | Average Hours | M.O.L. (inches) | M.O.D. (inches) | Incandescent Equivalent |
| Soft Daylight Light | 82 | 2750 | N/A | 24000 | 47.750 | 1.000 | N/A |
| Energy Star | DLC | Title 24 Compliant | Safety Rated | Safety Rating Type | Enclosed Rated | Dimmable | Warranty |
| N | N | N | N/A | N/A | N | N | N/A |

Order Multiple
QTY
25

APPLICATION SUGGESTIONS



Commercial

Sign /
Display