

## CLEANER, LUBRICANT & PRESERVATIVE

mil-spec





## **FEATURES**

- Performs in temperatures ranging from -65°F to 475°F, and after saltwater immersion
- Reduces metal-to-metal wear by protecting treated surfaces with an advanced boundary film
- Does not deteriorate under high temperatures and extreme pressure
- Displaces and loosens residue and contaminants from bearing areas
- Protects metals with special rust inhibitors



PART REF ID	PART #	DESCRIPTION
CLP-16-1	1009221	.68 oz. (20 ml) Squeeze Bottle
CLP-14-1	1350035	1 oz. (30ml) Needle Applicator Bottle
CLP-21-1	1350036	2 oz. (60ml) Spray Bottle
CLP-4-1	1009232	4 oz. (118 ml) Squeeze Bottle
CLP-5-1	1009236	1 Pint (473 ML) with Trigger Sprayer
CLP-7-1	1009241	1 U.S. GL. (3.785 L) Gallon Jug
CLP-8-1	1009245	1 L (1.032 Quart) Liquid Single
CLP-9-1	1346577	5L (1.32 gal) Liquid Single
CLP-2-1	1009226	4 oz. (113.4 g) Aerosol
CLP-12-1	1009218	12 oz. (340 g) Aerosol