

PROTECH[®]

TECHNICAL SPECIFICATION

Entry I FR X Type IIIA Ballistic Shield



General

Test Standard(s)	NIJ Standard – 0108.01 (Pass/Fail Only) – Type IIIA
US Patent No.	US 10,180,308 B2
Test Round(s)	9-mm, 124 gr. FMJ – 5 Impacts .44-Magnum, 240 gr. LSWCGC – 5 Impacts
Part Number	1301038 – PTA-S Entry I FR X 1301037 – PTA-S Entry I FR X 3P

Design – Shield Body

Armor Material	Polyethylene Composite
Size (approx.)	1301038 – Entry I FR X – 24" L x 36" W (60.9cm x 91.4cm) 1301037 – Entry I FR X 3P – 24" L x 36" W (60.9cm x 91.4cm)
Coverage (approx.)	1301038 – Entry I FR X – 683 in ² (4,406cm ²) 1301037 – Entry I FR X 3P – 683 in ² (4,406cm ²)
Outer Covering	Protective lightweight material with anti-spalling and chemical resistant characteristics

Design – Shield Viewport

Armor Materials	Acrylic/Polycarbonate Composite
Size (approx.)	7" L x 10" W (17.8 cm x 25.4cm) – Viewing are at widest points
Orientation	Multi-layered (strike face and body side) 2" overlapping design

PROTECH®

TECHNICAL SPECIFICATION

Entry I FR X Type IIIA Ballistic Shield

Features

Weight (approx.)	1301038 – Entry I FR X –	12.5 lbs. (5.6 kg)
	1301037 – Entry I FR X 3P –	12.5 lbs. (5.6 kg)
Curvature	18 Degrees	
Handle Type(s)	3- Position (3P), Ambidextrous Handle	
Standard Accessories	“SHERIFF” Decal 18” L x 3” W (46 cm x 8 cm) “POLICE” Decal 18” L x 3” W (46 cm x 8 cm) Forearm Pad Dual Rake Bars	

Options

Optional Accessories	Carry Bag	
	-	1002756 – Entry I FR X, Entry I FR X 3P
	Hood	
	-	1156828 – Entry I FR X, Entry I FR X 3P
	Viewport Cover Set	
	-	1158612 - Entry I FR X, Entry I FR X 3P
	FoxFury® Taker B50™ Light	
	-	1290188 - Entry I FR X, Entry I FR X 3P
	FoxFury® Taker B70™ Light	
	-	1223867 - Entry I FR X, Entry I FR X 3P
FoxFury® Taker B30™ Light		
-	1314778 - Entry I FR X, Entry I FR X 3P	
FoxFury® Taker B10™ Light		
-	1314777 - Entry I FR X, Entry I FR X 3P	

PROTECH[®]

TECHNICAL SPECIFICATION

Entry I FR X Type IIIA Ballistic Shield

Performance – Independently Tested

.44 Magnum 240 gr. SJHP	1,400 ft/s (± 50 ft/s) (427 m/s (± 15 m/s)) – 5 Impacts
Tokarev 7.62 x 25mm 85 gr. FMJ	1,530 ft/s (± 30 ft/s) (466 m/s (± 9 m/s)) – 5 Impacts
FN 5.7 x 28mm 40 gr. SS197 (Blue Tip)	1,740 avg. ft/s (530 avg. m/s) – 5 Impacts
FN 5.7 x 28mm 28 gr. SS195LF	2,075 avg ft/s (632 avg. m/s) – 5 Impacts
Winchester 9mm 127 gr. SXT	1,250 ft/s (± 30 ft/s) (381 m/s (± 9 m/s)) – 5 Impacts
Speer .357 SIG 125 gr. TMJ	1,470 ft/s (± 30 ft/s) (448 m/s (± 9 m/s)) – 5 Impacts
.22 Cal 17 gr. FSP	17 gr. V50 ≥ 2148 ft/s (655 m/s)

 **WARNING**

WARNING: This product can expose you to chemicals including Methylene chloride, BPA, Lead, Acrylonitrile, Ethyl Acrylate, Formaldehyde, or Methanol, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov.