

PROTECH[®]

TECHNICAL SPECIFICATION

Entry I X Type IIIA Ballistic Shield



General

| | |
|------------------|---|
| Test Standard(s) | NIJ Standard – 0108.01 (Pass/Fail Only) – Type IIIA |
| US Patent No. | US 10,180,308 B2 |
| Test Round(s) | 9-mm, 124 gr. FMJ – 5 Impacts .44-Magnum, 240 gr. LSWCGC – 5 Impacts |
| Part Number | 1301036 – PTA-S Entry I X 1223503 – PTA-S Entry I X 3P |

Design – Shield Body

| | |
|--------------------|---|
| Armor Material | Polyethylene Composite |
| Size (approx.) | 1301036 – Entry I X – 24" L x 36" W (60.9cm x 91.4cm) 1223503 – Entry I X 3P – 24" L x 36" W (60.9cm x 91.4cm) |
| Coverage (approx.) | 1301036 – Entry I X – 733 in ² (4,729 cm ²) 1223503 – Entry I X 3P – 733 in ² (4,729 cm ²) |
| Outer Covering | Protective lightweight material with anti-spalling and chemical resistant characteristics |

PROTECH[®]

TECHNICAL SPECIFICATION

Entry I X Type IIIA Ballistic Shield

Design – Shield Viewport

| | |
|-----------------|---|
| Armor Materials | Acrylic/Polycarbonate Composite |
| Size (approx.) | 7" L x 10" W (17.8 cm x 25.4cm) – Viewing are at widest points |
| Orientation | Multi-layered (strike face and body side) 2" overlapping design |

Features

| | |
|----------------------|--|
| Weight (approx.) | 1301036 – Entry I X – 13 lbs. (5.9 kg) 1223503 – Entry I X 3P – 13 lbs. (5.9 kg) |
| Curvature | 18 Degrees |
| Handle Type(s) | 3- Position (3P), Ambidextrous Handle |
| Standard Accessories | "SHERIFF" Decal 18" L x 3" W (46 cm x 8 cm) "POLICE" Decal 18" L x 3" W (46 cm x 8 cm) Forearm Pad Dual Rake Bars |

Options

| | |
|----------------------|--|
| Optional Accessories | Carry Bag - 1002756 – Entry I X, Entry I X 3P Hood - 1156828 – Entry I X, Entry I X 3P Viewport Cover Set - 1158612 – Entry I X, Entry I X 3P FoxFury [®] Taker B10™ Light - 1314777 - Entry I X, Entry I X 3P FoxFury [®] Taker B30™ Light - 1314778 - Entry I X, Entry I X 3P FoxFury [®] Taker B50™ Light - 1186181 - Entry I X, Entry I X 3P |
|----------------------|--|

PROTECH[®]

TECHNICAL SPECIFICATION

Entry I X Type IIIA Ballistic Shield

Performance – Independently Tested

| | |
|---------------------------------------|---|
| .44 Magnum 240 gr. SJHP | 1,400 ft/s (± 50 ft/s) (427 m/s (± 15 m/s)) – 5 Impacts |
| Tokarev 7.62 x 25mm 85 gr. FMJ | 1,530 ft/s (± 30 ft/s) (466 m/s (± 9 m/s)) – 5 Impacts |
| FN 5.7 x 28mm 40 gr. SS197 (Blue Tip) | 1,740 avg. ft/s (530 avg. m/s) – 5 Impacts |
| FN 5.7 x 28mm 28 gr. SS195LF | 2,075 avg ft/s (632 avg. m/s) – 5 Impacts |
| Winchester 9mm 127 gr. SXT | 1,250 ft/s (± 30 ft/s) (381 m/s (± 9 m/s)) – 5 Impacts |
| Speer .357 SIG 125 gr. TMJ | 1,470 ft/s (± 30 ft/s) (448 m/s (± 9 m/s)) – 5 Impacts |
| .22 Cal 17 gr. FSP | 17 gr. V50 ≥ 2148 ft/s (655 m/s) |

 **WARNING**

WARNING: This product can expose you to chemicals including Methylene chloride, BPA, Lead, Acrylonitrile, Ethyl Acrylate, Formaldehyde, or Methanol, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov.