



## Technical Specifications Model Assault III LW Type III Ballistic Shield



Part Number	Size	Coverage	Weight	Thickness
<b>Horizontal Handle</b>				
1362601	20" W x 36" L (50.8cm x 91.4cm)	601 in <sup>2</sup> (3,877 cm <sup>2</sup> )	20.4 lbs. (9.25 kg)	0.578" (14.7mm)
<b>3P Handle</b>				
1362603	20" W x 36" L (50.8cm x 91.4cm)	601 in <sup>2</sup> (3,877 cm <sup>2</sup> )	22.2 lbs. (10.07 kg)	0.578" (14.7mm)
<b>FoxFury® B70 Integrated Horizontal Handle 1200 Lumens</b>				
1362602	20" W x 36" L (50.8cm x 91.4cm)	601 in <sup>2</sup> (3,877 cm <sup>2</sup> )	22.0 lbs. (9.98 kg)	0.578" (14.7mm)

### NIJ Standard 0108.01 with NIJ0101.06 Shot Protocol Type III

**UHMWPE Composite**

**Ultra-lightweight PE material with chemical resistant characteristics**

**Structure - Flat**

**Ambidextrous Handle**

### Viewport Design

**Glass/ Polycarbonate**

**Size – 5" L x 7" W (12.7 cm x 17.8 cm)**

**Trapezoid Viewing area for increased vertical visibility**

### Standard Accessories

"Approved for Public Release"

**Forearm Pad**

**Forearm Strap**

**1001817 – POLICE Decal – 13” L x 4” W (33 cm x 10 cm)**

**1001818 – SHERIFF Decal – 13” L x 4” W (33 cm x 10 cm)**

**Optional Accessories**

**1184578 – Shield Support Hook Attachment**

**1002756 – Shield Carry Bag 26x36 tall**

**1002757 – Shield Hood – Medium 13.5x23**

**1355021 – Assault Viewport Lens 3 Layer Tear Off Kit**

**1186181 - FoxFury® Taker B50™ Light w/ 1000 Lumens**

**1314778 - FoxFury® Taker B30™ Light w/ 1000 Lumens**

**1314777 – FoxFury® Taker B10™ Light w/ 380 Lumens**

**BALLISTIC PERFORMANCE**

Includes Bolts and Viewport being shot.

Tested Rounds	6 Impacts minimum
5.56 x 45mm, 55 gr. M193	3200 fps ± 30 fps (975 m/s ± 9 m/s)
7.62 x 39mm, 123 gr. Mild Steel Core	2380 fps ± 30 fps (725 m/s ± 9m/s)
7.62 x 51mm, 147 gr. NATO (M80)	2750 fps ± 50 fps (838 m/s ± 15 m/s)
SHOT LOCATIONS	
<ul style="list-style-type: none"> <li>1 - Viewport</li> <li>2 - Transition shot between viewport and ballistics</li> <li>3 - Bolt – Direct Hit</li> <li>4 - Bolt – Side of Bolt – down the threads of the bolt</li> <li>5 - 100mm (3.94”) – 3 shot cluster</li> <li>6 - 3 shots in a direct line</li> </ul>	
Shots 1 and 2 are the outside shots (6-1 and 6-2)	
Shot 3 is in between these two shots (6-3)	
<ul style="list-style-type: none"> <li>7 - 30-degree angle shot</li> <li>8 - 1” edge shot</li> </ul>	

(see diagram below for shot locations)

January 15, 2024

“Approved for Public Release”

Diagram for Shot Locations.



**WARNING**

**WARNING:** This product can expose you to chemicals including Methylene chloride, BPA, Lead, Acrylonitrile, Ethyl Acrylate, Formaldehyde, or Methanol, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

January 15, 2024

“Approved for Public Release”