

# Technical Specifications**PRO**TECH<sup>®</sup>Model Assault III VP Type III Ballistic Shield

**3** Position Handle



Strike Side

**Horizontal Handle** 

Part Number	Size	Coverage	Weight
Horizontal Handle			
1352071	20" W x 36" L (50.8cm x 91.4cm)	720 in <sup>2</sup> (4,645cm <sup>2</sup> )	28.5 lbs. (12.9 kg)
Ambidextrous 3 Position Handle			
1355728	20" W x 36" L (50.8cm x 91.4cm)	720 in² (4,645cm²)	30.5 lbs. (13.8 kg)

## NIJ Standard 0108.01 Type III (Pass/Fail Only)

Polyethylene Composite Protective lightweight material with chemical resistant characteristics Curvature - Flat Ambidextrous Handle

Viewport Design Size – 5" L x 7" W (12.7 cm x 17.8 cm) – Viewing area at widest points

### **Standard Accessories**

Forearm Pad 1001817 - POLICE Decal – 18" L x 3" W (46 cm x 8 cm) 1001818 - SHERRIF Decal – 18" L x 3" W (46 cm x 8 cm)

March 1, 2023, Rev-C

"Approved for Public Release"



#### **Optional Accessories**

1184578 – Shield Support Hook Attachment		
1002756 – Shield Carry Bag 26x36 tall		
1002757 – Shield Hood – Medium 13.5x23		
1355021 – Assault Viewport Lens 3 Layer Tear Off Kit		
1186181 - FoxFury® Taker B50™ Light w/ 1000 Lumens		
1314778 - FoxFury® Taker B30™ Light w/ 600 Lumens		
1314777 – FoxFury® Taker B10™ Light w/ 380 Lumens		

#### **BALLISTIC PERFORMANCE**

Tested Rounds	5 Impacts	
7.62 x 51mm, 147 gr. NATO (M80)	2750 fps ± 50 fps (838 mps ± 15 mps)	
7.62mm x 39mm, 123 gr. Mild Steel Core	2380 fps ± 30 fps (725 mps ± 9mps)	
5.56mm x 45mm, 55 gr. M193	3200 fps ± 30 fps (975 mps ± 9 mps)	

BALLISTIC PERFORMANCE INCLUDES ALL BOLTS AND THE VIEWPORT



WARNING: This product can expose you to chemicals including Methylene chloride, BPA, Lead, Acrylonitrile, Ethyl Acrylate, Formaldehyde, or Methanol, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

"Approved for Public Release"

A BRAND OF THE SAFARILAND GROUP TOGETHER, WE SAVE LIVES\*