



ARMOR PROTECH®

Technical Specifications Model Assault II VP Type III Ballistic Shield



Part Number	Size	Coverage	Weight
Horizontal Handle			
1347352	16" W x 30" L (50.8cm x 91.4cm)	458 in ² (2,955 cm ²)	21.5 lbs. (9.8 kg)
Ambidextrous 3 Position Handle			
1355727	16" W x 30" L (50.8cm x 91.4cm)	458 in ² (2,955 cm ²)	23.5 lbs. (10.7 kg)

NIJ Standard 0108.01 Type III (Pass/Fail Only)

Polyethylene Composite

Protective lightweight material with chemical resistant characteristics

Curvature - Flat

Ambidextrous Handle

Viewport Design

Size – 5" L x 7" W (12.7 cm x 17.8 cm) – Viewing area at widest points

Standard Accessories

Forearm Pad

1001817 - POLICE Decal – 18" L x 3" W (46 cm x 8 cm)

1001818 - SHERRIF Decal – 18" L x 3" W (46 cm x 8 cm)

"Approved for Public Release"



Optional Accessories

1184578 – Shield Support Hook Attachment

1002756 – Shield Carry Bag 26x36 tall

1002757 – Shield Hood – Medium 13.5x23

1355021 – Assault Viewport Lens 3 Layer Tear Off Kit

1186181 - FoxFury® Taker B50™ Light w/ 1000 Lumens

1314778 - FoxFury® Taker B30™ Light w/ 600 Lumens

1314777 – FoxFury® Taker B10™ Light w/ 380 Lumens

BALLISTIC PERFORMANCE

Tested Rounds	5 Impacts
7.62 x 51mm, 147 gr. NATO (M80)	2750 fps ± 50 fps (838 mps ± 15 mps)
7.62mm x 39mm, 123 gr. Mild Steel Core	2380 fps ± 30 fps (725 mps ± 9mps)
5.56mm x 45mm, 55 gr. M193	3200 fps ± 30 fps (975 mps ± 9 mps)

BALLISTIC PERFORMANCE INCLUDES ALL BOLTS AND THE VIEWPORT

WARNING

WARNING: This product can expose you to chemicals including Methylene chloride, BPA, Lead, Acrylonitrile, Ethyl Acrylate, Formaldehyde, or Methanol, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

“Approved for Public Release”