



Technical Specifications Model X-CAL LP ICW Special Threat Plate



Shooter / Rectangle Cut – Multi Curve 7x9, 5x8 and 6x6 – Single Curve

Part Nu	ımber	Size	Weight
1166	518	10x12 MC SH	5.46 lbs. (2.47 kg)
1356	474	10x12 MC RE	6.00 lbs. (2.72 kg)
1190	595	8x10 MC RE	4.21 lbs. (1.91 kg)
1184	770	7x9 SC RE	3.30 lbs. (1.50 kg)
1184	769	5x8 SC RE	2.10 lbs. (0.95 kg)
1179	406	6x6 SC RE	1.81 lbs. (0.82 kg)

Independently Tested


Thickness: 0.4" [1.0 cm]

Ceramic Composite

Polyolefin Spall Coating

Shooters Cut and Rectangle Cut





BALLISTIC PERFORMANCE

Configurations below defeat 1 impact of the rounds specified					
7.62 x 51mm, 147 gr. NATO FMJ (M80) Velocity 2780 fps +/- 30 fps	I BA-3A00S-SX02 I	7.62 x 54Rmm, 150 gr. LPS Velocity 2610 +/- 30 fps	BA-2000S-SX02 BA-3A00S-SX02 BA-3A00S-SX03		
7.62 x 39mm, 119 gr. API BZ Velocity 2400 fps +/- 30 fps			BA-2000S-SM02 BA-3A00S-SM02		
5.56 x 45mm, 55 gr. M193 Velocity 3200 fps +/- 30 fps			BA-3A00S-XT03 BA-2000S-MR02		
5.56 x 45mm, 62 gr. M855 (SS109) Green Tip Velocity 3050 fps +/- 30 fps			BA-3A00S-MR02 BA-2000S-PX01		
7.62 X 39mm, 123 gr. MSC Velocity 2400 fps +/- 30 fps	BA-2000S-PX01 SIIIA-6.0		SIIIA-6.0		



WARNING: This product can expose you to chemicals including Methylene chloride, BPA, Lead, Acrylonitrile, Ethyl Acrylate, Formaldehyde, or Methanol, which are known the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

