

Kawasaki ER6/Ninja 650 Seat Cowl Part # 130222

Fitting Instructions

Fitting Kit:

- 2 x black powder-coated brackets – CFK11525
- 2 x M6 x 16mm counter sunk Allen bolts – CBOLM60013
- 2 x M6 counter sunk stainless steel washers – CWASM60006
- 2 x M6 rubber washers – CWASM60007
- 2 x ½” self tapping screws – CSCR0002
- 2 x flat steel washers – CWASM60001
- 1 x seat pad (fitted to colour matched cowl) – CPAD0315

Take the seat unit off the bike and using a 12mm spanner take out the two bolts holding each grab rail and remove both grab rails.

Fit the bracket marked 1 to the right hand side of the cowl with the bend toward the bottom edge, using one of the the M6 x 16mm countersunk bolts, stainless washer and rubber washer.

Fit the bracket marked 2 to the left side in the same manner.

Feed the seat cowl onto the seat unit from the rear, making sure the brackets clear the underside protrusions all the way along and that the rear end of the seat finally nestles centrally into the bottom lip of the cowl making sure the high line ridge across the middle of the seat tucks just slightly under the top front aperture of the cowl all the way across.

Fasten seat and cowl back down on the bike and make sure alignment of cowl is central and that it is pushed forward as far as possible with equally spaced shut lines on each side and ridge of seat is firmly tucked inside front aperture of cowl.

When totally happy with fit, remove the seat unit again taking care not to disturb position of cowl. Turn the seat unit upside down and using a 3mm drill bit, drill through the corresponding holes in the two front brackets and into the white plastic underside of the seat to take the two screws and steel washers supplied.

Tighten screws until firm and replace whole unit on bike.