## Kawasaki Z300 & EX300 2014

## FITTING INSTRUCTIONS TO BE FITTED BY A QUALIFIED TECHNICIAN



THIS SHEET INCLUDES FITTING INSTRUCTIONS FOR THE FOLLOWING PARTS:

Secondary Alternator Cover Part No. EC-Z300-2014-1-GBR / Secondary Clutch Cover Part No. EC-Z300-2014-2-GBR



## SECONDARY ALTERNATOR COVER PART NO. EC-Z300-2014-1-GBR

- 1. Remove nearside lower belly panel. The lower part of the main fairing panel will need to be loosened to allow for access to Bolt 4 in terms of its removal and replacement.
- 2. Remove 4 existing bolts from the stock Alternator cover, shown as position Bolt 1, 2, 3 & 4.
- 3. Place the Secondary Alternator Cover over the stock cover.
- 4. Assemble 4 replacement bolts loosely in the correct positions as shown.
- 5. Tighten bolts to a Torque of 11Nm as per  $Manufacturer's \ recommendations. \ \ DO\ NOT\ OVERTIGHTEN.$
- Replace lower belly panel.






## SECONDARY CLUTCH COVER PART NO. EC-Z300-2014-2-GBR

- Remove offside lower belly pan panel. 1.
- Remove 4 existing bolts from the stock Clutch cover, shown as position Bolt 1, 2, 3 & 4. 2.
- 3. Place the Secondary Clutch Cover over the stock cover.
- 4. Assemble 4 replacement bolts loosely in the correct positions as shown.

Replace lower belly pan panel.





EC-Z300-2014-1-GBR - EC-Z300-2014-2-GBR